



PYRAMEX
Perform At Your Peak

XSG® ANSI CE CSA



FOAM
PADDING



INCLUDES
STRAP

Flame resistant foam padding

Strap has quick fit retainer

Interchangeable temples and strap included



Part No.	Black Frame
GB4010ST ●●●	AF Clear H2X
GB4010STM ●●●	AF Clear H2MAX
GB4020ST ●●●	AF Gray H2X
GB4080ST ●●●	AF I/O Mirror



XSG Readers ANSI CSA



FOAM
PADDING



INCLUDES
STRAP

Part No.	Black Frame
GB4010STR15 ●●●	AF Clear H2X +1.5 Mag
GB4010STR20 ●●●	AF Clear H2X +2.0 Mag
GB4010STR25 ●●●	AF Clear H2X +2.5 Mag



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●), Canadian (CSA Z94.3) (●) or Ballistic (MIL-PRF-32432) (●) standards. For specific lens options visit our website or contact your sales representative.

XSG®

General Specifications

Weight: 28 gm
 PD: 68 mm
 Bridge: 13.7 mm
 Lens base: 8.0 curve
 Lens size diagonal: 66.3 mm
 Lens size vertical: 44 mm
 Lens thickness: 2.3 mm
 Strap length: 420 mm
 Overall length (lens - tip): 163 mm
 Overall width (hinge - hinge): 136.5 mm
 Closest point between temples: 56 mm
 Closest point between lens: 18.5 mm

Part No.	Lens Markings	Frame Markings
GB4010ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
GB4010STM	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
GB4020ST	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
GB4080ST	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light
 L2.5: 29% max visible light

Materials

Lens: polycarbonate
 Foam: polycarbonate & ethylene vinyl acetate (EVA)
 Frame: nylon
 Temples: polycarbonate & polyvinyl chloride (PVC)
 Strap: polyester
 Screw: stainless steel
 Nosepiece: ethylene vinyl acetate (EVA)

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

XSG Readers

General Specifications

Weight: 35 gm
 PD: 68 mm
 Bridge: 13.7 mm
 Lens base: 8.0 curve
 Lens size diagonal: 66.3 mm
 Lens size vertical: 44 mm
 Lens thickness: 2.3 mm
 Strap length: 420 mm
 Overall length (lens - tip): 163 mm
 Overall width (hinge - hinge): 136.5 mm
 Closest point between temples: 56 mm
 Closest point between lens: 18.5 mm

Part No.	Lens Markings	Frame Markings
GB4010STR15	P Z87 +	+1.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
GB4010STR20	P Z87 +	+2.00 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15
GB4010STR25	P Z87 +	+2.50 P Z87 - 2+ / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

Materials

Lens: polycarbonate
 Foam: polycarbonate & ethylene vinyl acetate (EVA)
 Frame: nylon
 Temples: polycarbonate & polyvinyl chloride (PVC)
 Strap: polyester
 Screw: stainless steel
 Nosepiece: ethylene vinyl acetate (EVA)

Frame Marking Symbols

+1.50: magnification of +1.5
 +2.00: magnification of +2.0
 +2.50: magnification of +2.5
 P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 - 2: Rx
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

