



RUST TOUGH®

Rust Tough® is a protective coating that can be applied direct to metal—no primer needed. This fast drying formula provides superior rust protection that resists scratches and abrasions.

- ✓ Direct-to-metal
- ✓ No primer needed
- ✓ Excellent gloss and color retention
- ✓ One coat coverage
- ✓ State-of-the-art corrosion protection

INDUSTRIAL USE ONLY!

krylonindustrial.com
1-800-247-3266

RECOMMENDED USES

- Steel
- Aluminum
- Ladders
- Bar Joints
- Hand Rails
- Conveyors
- Primed Metal
- Machinery
- Primed Wood
- Piping
- Fencing
- Storage Tanks
- Marine

SURFACE PREPARATION

Directions: WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. For more information, contact your local health authority. Prepare surface by removing dirt, grease, wax, moisture, rust and loose paint. Scuff-sand rusted, glossy or hard surfaces. If needed, prime bare or rusted metal with Krylon Rust Tough Gray (R00829) or Red (R00699) Primer. Wait 30 minutes before applying topcoat. Protect adjacent surfaces from overspray.

CLEAN-UP

Clean spray valve immediately after use by turning can upside-down and spraying until only clear gas comes out. Dispose of in accordance with local, state or federal regulations.

TECHNICAL DATA

Vehicle	Acrylic Alkyd Enamel
Finish	Flat, Semi-Gloss, Gloss
Flash Point	-20°
Weight/Gallon	6.41 lb/gal
VOC/MIR	65/1.40
Spread Rate	30-35 sq. feet
Shelf Life	60 months
Drying Time	To Touch: 30-60 minutes To Recoat: Anytime To Handle: Within 2 hours or after 48 hours
Dry Heat Resistance	300°
Gas Resistance	Film degradation, loss of gloss & staining
Oil Resistance	Pass
Clean Up	Mineral Spirits, Please follow suppliers instructions
Net Weight/Can Size	15 oz. / 20 oz.

APPLICATION

APPLICATION CONDITIONS

Use at 70°F for best operation. Shake can for 2 minutes after ball within begins to rattle. Repeat for 10 seconds after each minute of use. Test spray on inconspicuous area or scrap piece to check compatibility. For a smooth, professional finish, spray 6" to 8" from surface in a sweeping motion. Avoid runs and drips by applying several thin coats, rather than one heavy coat. Dries to touch in 30 to 60 minutes. Can be handled in 2 to 3 hours. Can be recoated within 2 hours or after 48 hours. EZ TOUCH® FANSPRAY® NOZZLE: You get professional-looking results with the EZ TOUCH FANSPRAY. It takes half as much finger pressure. The FANSPRAY covers better with less overspray. Change spray direction just by turning the square insert.

CAUTIONS

FOR INDUSTRIAL USE ONLY. Thoroughly review product label and SDS for safety and cautions prior to using this product. Please direct any questions or comments to your local Krylon Industrial Representative.

Note: The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, Krylon Products Group cannot make any warranties as to the end result. Please direct any questions or comments to 1-800-247-3266.

The information and recommendations set forth in the Product Data Sheet are based upon tests conducted by or on behalf of Krylon® Industrial. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Krylon® Industrial dealer or representative to obtain the most recent Product Data Sheet.