-Consistent Performance Long Lasting Shine

For over 50 years, high performing 3M[™] Floor Pads have been an industry leader. High performance aligns well with sustainability.

When compared to the nearest competitor, 3M floor pads:

- Remove deep scuff marks 7 times faster*
- Provide nearly 40% more aggressive floor stripping*
- Have 25% better cut on Schiefer test*
- Have 50% better burnishing durability*



*For additional Environmental, Health and Safety information, please refer to 3M[™] Floor Pads Technical Bulletin (78-8134-0152-4 Rev. A).

3M[™] Floor Pads A product you can rely on.


Every 3M[™] Floor Pad is made to high quality standards. And ongoing innovation and advancements in technology make 3M floor pads more effective than ever. It's no wonder we are the **#1 supplier worldwide**.

- Each floor pad in 3M's full line is engineered specifically for a particular maintenance task.
- 3M floor pad uniformity and quality helps produce:
 - less machine wobble and vibration.
 - less operator fatigue.
 - prolonged useful life of the pad.
 - better results on your floors.
- Uniform coating throughout every 3M floor pad helps produce a long, useful life, resulting in less pad usage.
 Plus 3M pads are washable and reusable.

All floor pads are not created equally.

The differences between floor pads may seem small. But when added up, they can make a big difference to your bottom line in terms of productivity and labor costs. Consider the following attributes of 3M floor pads that help set them apart from the competition:

- Uniform distribution of mineral abrasives throughout pad — not just on the surface — offers impressive performance and a long, useful life.
- Individually separated and coated fibers help produce more consistent, high-quality results.
- The combination of highly conformable fibers help to provide maximum pad-to-floor contact.



- Fibers uniformly coated with resin and mineral throughout entire pad, producing more consistent results
- Combination of highly conformable fibers help to maximize the pad-to-floor contact



long useful life

washable

reusable

- Fibers randomly coated with resin and mineral, which can produce inconsistent results
- Larger fibers are less conformable, providing fewer contact points with the floor

Choose The Right 3M Floor Pad For The Job

Maintenance Operation	Equipment Speed	First Choice			
Stripping To remove finish, sealer and contaminants	Rotary or Automatic		3M™ High Productivity Pad 7300		
from the floor surface. Done at the start of a maintenance program and at times when scrubbing will not achieve the desired results.	Low Speed 175–600 RPM	·	Our most aggressive stripping pad. Unique open construction resists loading and clogging. For fast removal of finish and proven consistent stripping.		
Scrubbing	Rotary or Automatic		Scotch-Brite™ Surface Prep Pad		
Done prior to replacing worn finish; provides a fresh new surface to maintain.	Low Speed 175–600 RPM	an an a	Heavy duty scrubbing for 2–4 coat removal prior to recoating.		
Cleaning	Rotary or Automatic		3M [™] TopLine Autoscrubber Pad 5000		
To remove light soil and other contaminants.	Low Speed 175–600 RPM		Scrubs and cleans without dulling the finish. Open construction resists clogging. Ideal for use on an autoscrubber.		
Buffing To remove scuffs and black heel marks and enhance floor appearance.	Rotary		3M [™] Red Buffer Pad 5100 Designed for everyday cleaning and light scrubbing to		
	Low Speed 175–600 RPM		remove light soil, scuff marks and black heel marks.		
Burnishing To repair finish and improve gloss and image clarity of floor surface. Scuff & Mark Removal	Electric Battery Propane		3M[™] Eraser Burnish Pad 3600 Removes black marks and returns gloss in fewer passes than other pads while producing less dust. Ideal for harder finishes and high traffic areas. Excellent durability and minimal finish removal.		
	Ultra High Speed 1500 RPM & Above				
Post Close	Electric Battery Propane		3M [™] TopLine Speed Burnish Pad 3200 Optimizes UHS burnishing on a wide variety of finishes.		
Best Gloss	Ultra High Speed 1500 RPM & Above		Combines black mark removal and gloss generation in one pad.		
Soft Finish	Electric Battery Propane		3M [™] Sky Blue Hi-Performance Burnish Pad 3050 Restores gloss to dull floors. Designed for frequent burnishing		
	Ultra High Speed 1500 RPM & Above		with less dust, point build-up and burning, this pad is an excellent addition to 3M's high-performing line of burnishing pads.		
Diamond-Coated Floor Pads	Rotary, Automatic, Electric, Battery or Propane	344	Scotch-Brite [™] Sienna Diamond Floor Pad Plus Diamond coated floor pads for cleaning and conditioning worn		
Use to clean and condition worn and dull stone floors.	Low to Ultra High Speed 175–1500 RPM & Above	Seoreth Train -	and dull marble, terrazzo, slate and polished concrete flooring.		
Diamond-Coated Floor Pads	Rotary, Automatic, Electric, Battery or Propane		Scotch-Brite [™] Purple Diamond Floor Pad Plus Diamond coated floor pads for cleaning and polishing marble,		
Use to clean and polish stone floors.	Low to Ultra High Speed 175–1500 RPM & Above	scell Law	terrazzo, slate and polished concrete flooring.		

Greener Solutions



The polyester fiber used to make a range of floor pads* contains a minimum of 50% post-consumer recycled content. The recycled polyester fiber used is third-party certified for post-consumer recycled content.

*3M[™] Brand Floor Pad families include 3200, 3300, 3400, 3500, 5000 and 5100.

Alternate	System Procedures	
3M [™] Black Stripper Pad 7200 Standard of the industry. Consistent proven performance. Long pad life.	3M [™] Brown Stripper Pad 7100 Conformable stripping pad for uneven floors. Strips prior to refinishing. Super heavy duty scrubbing for 2–4 coat removal prior to recoating.	 Dust mop Mask off delicate surface Apply properly diluted stripping solution Let solution dwell 5 minutes Strip with floor machine and pad Pick up dirty solution Detail damp mop Let dry and dust mop prior to applying finish
3M [™] Blue Cleaner Pad 5300 Heavy duty scrubbing for 1–2 coat removal prior to recoating.		 Dust mop Apply properly diluted scrubbing solution Scrub with floor machine and pad Pick up dirty solution Detail damp mop Let dry, dust mop prior to buffing or applying finish
3M [™] Red Buffer Pad 5100 Designed for everyday cleaning and light scrubbing to remove light soil, scuff marks and black heel marks.	3M [™] White Super Polish Pad 4100 Used for light cleaning to help remove soil and scuff marks with minimal dulling of finish. Can also be used to polish wood floors.	 Dust mop Apply properly diluted cleaning solution Clean with floor machine and pad Pick up dirty solution Let dry prior to buffing
3M [™] White Super Polish Pad 4100 Used for light cleaning to help remove soil and scuff marks with minimal dulling of finish. Can also be used to polish wood floors.		 Dust mop Buff only clean floors Apply spray buff to floor Buff to a high gloss using overlapping passes Dust mop
■ SM [™] Natural Blend Tan Pad 3500 Blend of natural and synthetic fibers. For use on harder finishes and high traffic conditions. Removes marks and scuffs while polishing.	3M [™] Tan Burnish Pad 3400 Produces good gloss improvement while removing scuffs and marks. Exceptional durability and life. For use on harder finishes and high traffic conditions.	
3M [™] Natural Blend White Pad 3300 Blend of natural and synthetic fibers. Excellent results on a wide variety of finishes and traffic conditions. Provides consistent high gloss while minimizing swirl marks.		 Dust mop Burnish only clean floors Burnish to a high gloss using overlapping passes Dust mop
3M [™] Aqua Burnish Pad 3100 Produces good gloss improvement. Exceptional durability and life. The soft finish problem solver.		
		 Dust mop 6–12 passes with Scotch-Brite[™] Sienna Diamond Floor Pad with automatic floor machine or burnisher 6–12 passes with Scotch-Brite[™] Purple Diamond Floor Pad Plus with automatic floor machine or burnisher Use 3M[™] TopLine Autoscrubber 5000 to maintain floor appearance When shine level begins to fade, use Scotch-Brite[™] Purple Diamond Floor Pad Plus again

Competitive Floor Pad Cross-Reference									
Operation	3M [™] Floor Pads	Niagara™	ETC of Henderson	Americo	Glit [®] /Microtron [®]	Norton Abrasives	ACS/Scrubble [®]		
Stripping	3M™ High Productivity Pad 7300	 High Performance 7400N 	• Razorback®	• The Dominator	 Emerald II Safire[®] 66 High Performance 	Ultra Blue Hi Pro Stripping	• Emerald Hy-Pro		
	3M™ Black Stripper Pad 7200	Black Stripping 7200N	Black-Strip	 Black Strip 	Black Stripping	Black Super Strip	Black Strip		
	3M [™] Brown Stripper Pad 7100	N/A	Brown-Strip Boss Hawg®	• Brown Strip	Brown Stripping	N/A	Brown Strip		
Scrubbing	Scotch-Brite™ Surface Preparation Pad	N/A	N/A	 Maroon HD Maroon Eco Prep 	N/A	Enviro Stripping Pad	Maroon Thin Line		
	3M™ Blue Cleaner Pad 5300	 Green Scrub 5400N Blue Cleaning 5300N 	Green-Scrub Blue-Cleaner	Green Scrub Blue Cleaner	Green Scrubbing Blue Cleaner	 Green Super Scrub Blue Super Clean 	Green ScrubberBlue Cleaner		
Cleaning	3M™ TopLine Autoscrubber Pad 5000	N/A	N/A	 Flamingo Auto Scrub™ 	Coral Pre-Burnishing	N/A	N/A		
	3M [™] Red Buffer Pad 5100	 Red Buffing 5100N 	 Gorilla[®] Red-Spray Buff 	Red Buff	Red Spray Buffing	Red Buffer	Red Buffing		
	3M™ White Super Polish Pad 4100	White Polishing 4100N	• Gorilla® White-Polish	White Polish	White Super Polishing	White Super Gloss	White Polishing		
Buffing	3M™ Red Buffer Pad 5100	Red Buffing 5100N	 Gorilla[®] Red-Spray Buff Gorilla[®] Tan-Buff 	 Red Buff Tan Buff	 Red Spray Buffing 40-D Red Tan Buff Polishing 	 Red Buffer Champagne Polish & Burnish 	Red Buffing		
	3M [™] White Super Polish Pad 4100	White Polishing 4100N	 Gorilla[®] Soft White-Polish 	White Polish	White Super Polishing	White Super Gloss	White Polishing		
Burnishing	3M™ Eraser Burnish Pad 3600	N/A	N/A	N/A	N/A	N/A	N/A		
Most Aggressive	3M™ Natural Blend Tan Pad 3500	 Natural Tan Hog's Hair 3500 Super Hog's Hair 3700N Natural Tan Hog's 3500N 	• Gorilla® • 2001 Gorilla® • Jaguar® • 2001 Jaguar®	PorkoPorko Plus	 Buckaroo® Natural Hair Jackeroo® Natural Hair 	• Ultra Grizzly Bear	• Hair Blend Extra Heavy		
	3M [™] Tan Burnish Pad 3400	Tan Burnishing 3400N	N/A	 Image Beige Burnishing 	UHS Tan Burnishing Champagne Burnishing	• Pink "TOPSHINE"	N/A		
	3M™ Natural Blend White Pad 3300	Natural White Burnishing 3300N	 Gorilla Lite[®] 2001 Gorilla Lite[®] Blue Jay[®] Superspeed Rubberized[®] 	Porko Elite Combo	• Jackeroo® Lite Natural Hair	• Grizzly Bear Lite	• Hair Blend Lite		
Least Aggressive	3M™ TopLine Speed Burnish Pad 3200	N/A	• 2001 Superspeed Rubberized®	• Aqua Burnishing	 Beige Poly Thermal Burnishing 100D Neutral Poly Thermal Peach Beige Light Burnishing Joey[®] Specialty Burnishing CocoPad[®] 	• Thermal Burnish	Poly Thermal Pink Burnishing		
	3M™ Aqua Burnish Pad 3100	Aqua Burnishing 3100N	 Aqua Plus[®] 2001 Aqua Plus[®] 	• Aqua Burnishing	UHS Aqua Burnishing	• Aqua Ultra	Aqua Burnishing		
	3M™ Sky Blue Hi-Performance Burnish Pad 3050	N/A	 2001[®] Soft White Blue Ace[®] 	• Luster Lite	Blue Ice [®] Burnishing	N/A	Blue Velvet		
Diamond- Coated Floor Pads	Scotch-Brite™ Sienna Diamond Floor Pad Plus	N/A	 Diamond by Gorilla[®] 800 White Diamond by Gorilla[®] 1500 Yellow 	 Twister[™] White Twister[™] Yellow 	N/A	Coarse GritMedium Grit	Cyclone D 800		
Cleans and polishes stone floors	Scotch-Brite [™] Purple Diamond Floor Pad Plus	N/A	• Diamond by Gorilla [®] 3000 Green	● Twister™ Green	N/A	Fine GritVery Fine Grit	Cyclone D 3000		

Environmentally Preferable Solutions for Hard Floor Maintenance and Protection

Fewer Chemicals Used

The Scotch-Brite™ Diamond Floor Pad Plus System allows the maintenance and polishing of stone, marble and terrazzo flooring without the use of floor finishes and strippers. Eliminating the use of floor finish and floor stripping chemicals in a stone floor maintenance program can help reduce chemical exposure for your workers and release to the environment.

Life Cycle Management

3M sustainability includes developing new products through a Life Cycle Management (LCM) process. LCM includes a comprehensive review of a product's potential health, safety, environmental and regulatory impact throughout its lifetime. The LCM process is a cradle-to-grave approach to product development. It includes raw material acquisition, transportation, manufacturing, use and disposal. 3M technical experts in toxicology, industrial hygiene, environmental engineering, product stewardship and product safety all participate in the LCM process. Their guidance in the product development process helps ensure that safe, environmentally preferable, functional solutions are delivered to our customers.

Sustainability

3M stands behind its floor pads and other products for performance, safety. minimizing environmental impact and general customer satisfaction.

3M[™] Floor Pads are washable and reusable, lasting longer and outperforming other brands to help postpone landfill disposal. The right abrasive paired with the proper fibers using proprietary manufacturing techniques yields a pad that is durable and reusable, helping to postpone end-of-life disposal to landfills.

The polyester fiber used to make a range of floor pads* contains a minimum of 50% post-consumer recycled content. The recycled polyester fiber used is third-party certified for post-consumer recycled content.

*3M[™] Floor Pad families include: 3200, 3300, 3400, 3500, 5000 and 5100.

How to Reach Us

For more information on 3M[™] Floor Pads or to place an order, call your local 3M distributor. Or, for the name of your distributor, call 1-800-852-9722. To speak to a technical support person, call 1-800-626-8578. For general assistance, call 1-800-3M-HELPS.



3M Commercial Solutions Division 3M Center Building 220-12E-04 St. Paul, MN 55144-1000

www.3M.com/facility

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed. Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors than can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is a fit for user's particular purpose and suitable for user's method of application. Warranty and Limited Remedy: 3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

For additional Environmental, Health and Safety information, please refer to 3M[™] Floor Pads Technical Bulletin (78-8134-0152-4 Rev. A). Trizact Diamond HX Discs are intended for wet application use only. Do not use dry.

3M and Scotch-Brite are trademarks of 3M. Used under license in Canada. All other trademarks are property of their respective owners.

Please recycle. Printed in U.S.A. © 3M 2015. All rights reserved. 78-8134-0420-5 Rev. C