



# XHD SLOTTED SCREWDRIVERS W/HEX BLADES & BOLSTERS

### **Premium Comfort Grip Handles and Blades**

Product Code	Overall Length (Inches)	Blade Length (Inches)	Tip Width (Inches)
038.055.100	8 1/2"	5	7/32
038.065.125	10	6	1/4
038.080.150	11 1/2"	7	5/16
038.100.175	12 1/2"	7	3/8
038.120.200	13 1/2"	8	1/2
038.140.200	13 1/2"	9	9/16

#### **Features**

- Metal striking cap at top of handle gives ultimate protection during jobs requiring high impact and added force
- Thru-Blade shank continues through the handle before contacting the metal striking cap for ultimate strength
- Elastomer surface and double shaped handle for added comfort and maximum turning power
- Rudolite® plastic provides high impact resistance to the tool and a perfect joint between the handle and shank
- Black oxide tips prevent chipping of chrome to reduce possible contamination at work location





Thru-Blade shank continues through the handle before contacting the metal striking cap for ultimate strength





038.065.125



## **ERGO® SLOTTED SCREWDRIVERS WITH BOLSTER**

#### **Three Component Handle with Black Oxide Tips and Bolster**

Product Code	Overall Length (Inches)	Blade Length (Inches)	Tip Width (Inches)
BE-8158	9 3/4	5	7/32
BE-8160	9 <sup>3</sup> / <sub>4</sub>	5	5/16
BE-8159	10 <sup>3</sup> / <sub>4</sub>	6	1/4
BE-8260	11 <sup>3</sup> / <sub>4</sub>	7	5/16
BE-8865 **	13 <sup>1</sup> / <sub>2</sub>	7	5/16
BE-8870 **	13 <sup>1</sup> / <sub>2</sub>	7	3/8
BE-8880 **	14 <sup>1</sup> / <sub>2</sub>	8	1/2
BE-8890 **	14 <sup>1</sup> / <sub>2</sub>	8	9/16

\*\* Dual grip handle for two-handed operation provides extra torque when necessary

#### **Features**

- The three component ergonomically designed handle provides comfort and maximum grip even with oily hands.
- Color coded handles indicates tip type and show tip type symbol on bottom of handle for quick identification.
- Black oxide tips prevent chipping of chrome to reduce possible contamination at work location.
- Blades are equipped with bolster for use with wrench when extra torque is required.









