



Copper Coat® Aerosol, 9 Wt Oz
 No. 401612 | Item# 1006077 | Case# 1006076

Product Description	High temperature, high quality aerosol metallic gasket sealer. Prevents compression loss on premium gaskets. Ideal for head and intake gaskets.
Applications	Automatic transmissions, cover plates, diesel heads, high compression engines, hi-speed turbine superchargers, hydraulic pumps
Unit Package Description	12 Ounce Aerosol
Brand	K&W
Generic Description 1	Gasket Compound
Net Fill	9 Wt Oz
UPC Code	078372016127
Unit Dimensions	6.38H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	7H x 8.5W x 11D in
Cases Per Pallet	126
Case Weight	10 lbs
I 2 of 5 Code	10078372016124
Appearance	Copper Liquid
Flash point (F)	-20°F
Flash point (C)	-29°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.74
Plastic Safe	Yes
Evaporation Rate	Fast
Curing Time	Not Determined
Working Temp (F)	-80 to 400°F
Working Temp (C)	Not Determined
Viscosity @68 F cP	Not Determined
Propellant	Hydrocarbon

Last revised: 10/8/2019
 Page 1 of 2





Aerosol Flammability Level	II
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	54.23
VOC g/L (Consumer Product def)	399
VOC lbs/gal (Consumer Prod def)	3.33
VOC Category	Automotive Engine Compartment Spray Adhesive
Removal (How To)	Gasket remover