



Driller Red Grease Extreme Pressure Lithium Complex Grease, 35 Lbs

No. SL3650 | Item# 1007960

Product Description	Driller Red Grease is a NLGI #2 Red Grease which offer superior protection to lubricate a wide variety of severe duty drilling, industrial, mining and construction equipment. Timken load of 80 lbs.
Applications	Drilling and Mining applications, backing plates, ball joints, chassis points, construction ball & roller bearings, idler bearings, industrial applications, pillow block bearings, sprocket bearings, U-joints, water pumps, wheel bearings
Unit Package Description	35 Pound Pail
Brand	CRC
Generic Description 1	Extreme Pressure Lithium Complex Grease
Net Fill	35 Lb
UPC Code	072213365009
Unit Dimensions	15H x 12W x 12D in
Units Per Case	1
Case Dimensions	15H x 12W x 12D in
Cases Per Pallet	36
Case Weight	40 lbs
I 2 of 5 Code	30072213365000
Appearance	Red, Smooth, Tacky
Base Type	Lithium Complex
Flash point (F)	302°F
Flash point (C)	150°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.93
NLGI Grade	2
Timken OK Load Lbs.	80 Lbs
Plastic Safe	Yes
Dielectric Strength	Not Determined

Last revised: 9/4/2019
Page 1 of 2





Working Temp (F)	-10 to 400°F
Working Temp (C)	-23 to 204°C
4 Ball EP	315 Kgf
4 Ball Wear	0.45
Drop Point	550°F
Leakage	2.0
Low Temp Torque	Not Determined
Oil Separation	1.0
Oxidation Stability	Not Determined
Pour Point (F)	Not Determined
Pour Point (C)	Not Determined
Water Washout	2.5 at 175°F
Worked Penetration	265 to 295
Propellant	None
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	Not Determined
VOC g/L (Consumer Product def)	Not Determined
VOC lbs/gal (Consumer Prod def)	Not Determined
VOC Category	Not Regulated
Removal (How To)	Remove with a degreaser.

Last revised: 9/4/2019
Page 2 of 2