

Steel Dixon™ Hose Menders



• They are not for compressible products such as air, nitrogen or steam.

- The working pressure may vary with the construction of the hose, the type of clamping system used and the application. Consult Dixon™ for recommendations.
- In accordance with the ARPM bulletin for oil suction and discharge hose, a coupled length of hose in any size, should be tested to 1½ times the working pressure and held for fifteen minutes without leaking or coupling movement. For additional information and detailed instruction on testing procedures, see the Association for Rubber Products Manufacturer's (ARPM) handbook or visit ARPMINC.com.

G



| Size | Zinc Plated Steel | | Opt Qty | 316 Stainless Steel | | Opt Qty |
|------|----------------------------|---------------|---------|---------------------|----------------|---------|
| | Part # | Price/E | | Part # | Price/E | |
| ¼" | DMA | \$7.65 | 200 | RDMA | \$28.00 | 100 |
| ⅜" | DMB | 7.80 | 100 | RDMB | 32.65 | 100 |
| ½" | DM1 | 7.75 | 50 | RDM1 | 28.15 | 50 |
| ⅝" | DM5 | 7.95 | 50 | --- | --- | --- |
| ¾" | DM6 | 7.15 | 50 | RDM6 | 58.00 | 50 |
| 1" | DM11 | 6.80 | 50 | RDM11 | 61.00 | 50 |
| 1¼" | DM16 | 9.05 | 50 | RDM16 | 64.50 | 5 |
| 1⅜" | DM18 | 25.55 | 50 | --- | --- | --- |
| 1½" | DM21 | 10.25 | 50 | RDM21 | 73.50 | 50 |
| 1½" | DMXL21 ¹ | 24.15 | 25 | --- | --- | --- |
| 2" | DM26 | 11.55 | 50 | RDM26 | 82.70 | 10 |
| 2" | DMXL26 ¹ | 29.05 | 25 | --- | --- | --- |
| 2½" | DM31 | 18.65 | 25 | --- | --- | --- |
| 3" | DM36 | 22.50 | 20 | RDM36 | 183.30 | 5 |
| 4" | DM46 | 41.40 | 10 | RDM46 | 216.30 | 5 |
| 5" | DM51 | 130.00 | 5 | --- | --- | --- |
| 6" | DM66 | 100.55 | 4 | --- | --- | --- |
| 8" | DM86 | 218.00 | 1 | --- | --- | --- |
| 10" | DM100 | 335.00 | 1 | --- | --- | --- |
| 12" | DM120 | 512.30 | 1 | --- | --- | --- |

¹ XL series has extra long shank

Steel King™ Hose Menders



• They are not for compressible products such as air, nitrogen or steam.

- The working pressure may vary with the construction of the hose, the type of clamping system used and the application. Consult Dixon™ for recommendations.
- In accordance with the ARPM bulletin for oil suction and discharge hose, a coupled length of hose in any size, should be tested to 1½ times the working pressure and held for fifteen minutes without leaking or coupling movement. For additional information and detailed instruction on testing procedures, see the Association for Rubber Products Manufacturer's (ARPM) handbook or visit ARPMINC.com.



for 1 clamp each end



for 2 clamps each end

for 1 clamp each end

for 2 clamps each end

| Size | Steel | | Steel | |
|-------|--------------|---------------|--------------|----------------|
| | Part # | Price/E | Part # | Price/E |
| ¼" | KM21 | \$7.65 | --- | --- |
| 5/16" | KM251 | 8.00 | --- | --- |
| ½" | KM41 | 8.80 | KM42 | \$11.90 |
| ⅝" | KM51 | 11.30 | KM52 | 12.10 |
| ¾" | KM61 | 8.75 | KM62 | 11.60 |
| 1" | KM81 | 8.60 | KM82 | 11.90 |
| 1¼" | KM101 | 7.80 | KM102 | 13.65 |
| 1½" | KM121 | 11.10 | KM122 | 20.75 |
| 2" | --- | --- | KM162 | 28.70 |

Dixon™ 316 Stainless Steel Menders



| Size | Length | Stainless Steel | |
|------|---------|-----------------|----------------|
| | | Part # | Price/E |
| ¼" | 2-1/32" | RM2 | \$15.20 |
| ⅜" | 2-1/16" | RM3 | 16.30 |
| ½" | 2-1/16" | RM4 | 24.45 |
| ¾" | 2½" | RM6 | 31.40 |