# PROBRANDS

#### SAFETY DATA SHEET

#### 1. Identification

Product identifier Dykem® Brite-Mark® Fine Line- Red

Other means of identification

Part Number 41002

Recommended use Not available.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands

Address 805 E. Old 56 Highway

Olathe, KS 66061

Country (U.S.A.)

Tel: +1 800-443-9536

In Case of Emergency 1-800-535-5053 (Infotrac)

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or

dizziness.

**Precautionary statement** 

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye

protection/face protection.

**Response** If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get

medical advice/attention. In case of fire: Use appropriate media to extinguish.

**Storage** Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

#### 3. Composition/information on ingredients

#### **Mixtures**

Material name: Dykem® Brite-Mark® Fine Line- Red
41002 Version #: 01 Issue date: 12-01-2021 1 / 10

Chemical name	Common name and synonyms	CAS number	%
ethanol		64-17-5	30 - 50
1-methoxypropan-2-ol		107-98-2	20 - 30
Titanium Dioxide		13463-67-7	10 - 20
propan-2-ol		67-63-0	5 - 10
C.I. Pigment Red 254		84632-65-5	0.01 - 5

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical Skin contact

attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important symptoms/effects, acute and

delaved

Indication of immediate medical attention and special treatment needed

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation.

immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the **General information** material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

#### **Environmental precautions**

#### 7. Handling and storage

#### Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
ethanol (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
propan-2-ol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. California Code of Regulations	, Title 8, Section 5155. Airbo	rne Contaminants	
Components	Туре	Value	
1-methoxypropan-2-ol (CAS 107-98-2)	PEL	360 mg/m3	
		100 ppm	
	STEL	540 mg/m3	
		150 ppm	
ethanol (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
propan-2-ol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
	STEL	1225 mg/m3	
		500 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
1-methoxypropan-2-ol (CAS 107-98-2)	STEL	100 ppm	
	TWA	50 ppm	
ethanol (CAS 64-17-5)	STEL	1000 ppm	
propan-2-ol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	
1-methoxypropan-2-ol (CAS 107-98-2)	STEL	540 mg/m3	
		150 ppm	
	TWA	360 mg/m3	

# US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value 100 ppm ethanol (CAS 64-17-5) TWA 1900 mg/m3 propan-2-ol (CAS 67-63-0) STEL 1225 mg/m3 500 ppm TWA 980 mg/m3

#### **Biological limit values**

**ACGIH Biological Exposure Indices** 

Components	Value	Determinant	Specimen	Sampling Time
propan-2-ol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

#### US - California OELs: Skin designation

1-methoxypropan-2-ol (CAS 107-98-2)

Can be absorbed through the skin.

980 mg/m3 400 ppm

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

**Respiratory protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

#### 9. Physical and chemical properties

**Appearance** 

Physical state Liquid. **Form** Liquid. Color Not available. Odor Mild. Solvent. **Odor threshold** Not available. 7.5 - 8.1pН Melting point/freezing point Not available. 212 °F (100 °C) Initial boiling point and boiling range Flash point 62.6 °F (17.0 °C) **Evaporation rate** Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

Flammability (solid, gas)

(%)

Not available.

Not applicable.

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density 0.98 - 1.13

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity 15 - 20 cP

Other information

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

#### 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

**Conditions to avoid**Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong acids. Strong oxidizing agents. Chlorine. Isocyanates.

Hazardous decomposition

products

Carbon oxides.

#### 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation** May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

**Skin contact** No adverse effects due to skin contact are expected.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

#### Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components Species Test Results

1-methoxypropan-2-ol (CAS 107-98-2)

Acute Dermal

LD50 Rat > 2000 mg/kg

Inhalation

LC50 - 55 mg/l, 4 Hours

Oral

LD50 Rat > 2000 mg/kg

C.I. Pigment Red 254 (CAS 84632-65-5)

Acute Dermal

LD50 - > 2000 mg/kg

Material name: Dykem® Brite-Mark® Fine Line- Red 41002 Version #: 01 Issue date: 12-01-2021

**Species Test Results** Components Oral LD50 Rat > 2000 mg/kg ethanol (CAS 64-17-5) Acute Inhalation Vapor Rat LC50 51 mg/l, 6 Hours propan-2-ol (CAS 67-63-0) **Acute** Inhalation LC50 51 mg/l, 8 Hours Oral LD50 Rat 4.7 g/kg Titanium Dioxide (CAS 13463-67-7) **Acute** Inhalation LC50 Rat > 2.3 mg/l, 4 Hours Oral

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Rat

Serious eye damage/eye

LD50

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

**ACGIH Carcinogens** 

1-methoxypropan-2-ol (CAS 107-98-2)

propan-2-ol (CAS 67-63-0)

A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

**US. National Toxicology Program (NTP) Report on Carcinogens** 

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

> 2000 mg/kg

Components Species Test Results

ethanol (CAS 64-17-5)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) 7.7 - 11.2 mg/l, 48 hours

Fish LC50 Rainbow trout, donaldson trout 42 mg/l, 4 days

(Oncorhynchus mykiss)

propan-2-ol (CAS 67-63-0)

Aquatic

Acute

Fish LC50 Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours

Titanium Dioxide (CAS 13463-67-7)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) > 1000 mg/l, 48 hours
Fish LC50 Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours

Persistence and degradability 
No data is available on the degradability of any ingredients in the mixture.

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

1-methoxypropan-2-ol -0.49 ethanol -0.31 propan-2-ol 0.05

Mobility in soil Not established.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1263 UN proper shipping name Paint

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group ||

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**Special provisions** 149, 367, B52, IB2, T4, TP1, TP8, TP28

Packaging exceptions 150
Packaging non bulk 173
Packaging bulk 242

**IATA** 

UN number UN1263 UN proper shipping name Paint Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IMDG** 

UN number UN1263 UN proper shipping name Paint

Transport hazard class(es)

Class 3
Subsidiary risk Packing group II
Environmental hazards

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

#### DOT



IATA; IMDG



#### 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

**Classified hazard** 

Flammable (gases, aerosols, liquids, or solids)

categories Serious eye damage or eye irritation

Yes

Specific target organ toxicity (single or repeated exposure)

#### SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

ethanol (CAS 64-17-5) Low priority propan-2-ol (CAS 67-63-0) Low priority

#### **US** state regulations

#### US. New Jersey Worker and Community Right-to-Know Act

1-methoxypropan-2-ol (CAS 107-98-2) ethanol (CAS 64-17-5) propan-2-ol (CAS 67-63-0) Titanium Dioxide (CAS 13463-67-7)

#### California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

## US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1-methoxypropan-2-ol (CAS 107-98-2) propan-2-ol (CAS 67-63-0) Titanium Dioxide (CAS 13463-67-7)

#### **International Inventories**

Country(s) or region

Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
•	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

#### 16. Other information, including date of preparation or last revision

Inventory name

**Issue date** 12-01-2021

Version # 01

Material name: Dykem® Brite-Mark® Fine Line- Red

41002 Version #: 01 Issue date: 12-01-2021

On inventory (yes/no)\*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.