

Revision Number: 001.4 Issue date: 01/22/2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE LB 8034 SYN. GREASE HIGH IDH number: 457453

PERFORM. known as ViperLube(TM)

Product type:LubricantItem number:36780Restriction of Use:None identifiedRegion:United States

Company address:Contact information:Henkel CorporationTelephone: (860) 571-5100One Henkel WayMEDICAL EMERGENCY P

One Henkel Way

MEDICAL EMERGENCY Phone: Poison Control Center
Rocky Hill, Connecticut 06067

1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE DAMAGE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Wash thoroughly after handling. Wear eye and face protection. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing.

several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Immediately call a poison control center or physician. If skin irritation occurs: Get medical

attention. Take off contaminated clothing.

Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Zinc oxide	1314-13-2	5 - 10
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	5 - 10
Reinforcing filler	Proprietary	5 - 10

IDH number: 457453 Product name: LOCTITE LB 8034 SYN. GREASE HIGH PERFORM. known as ViperLube(TM)

Page 1 of 6

Alkyl Benzene	Proprietary	1 - 5
Filler	Proprietary	1 - 5
Sulfonic Ester	Proprietary	1 - 5
Sulfonic Ester	Proprietary	0.1 - 1
Filler	Proprietary	0.1 - 1

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: If high pressure forces the product under the skin get immediate medical

attention. If hot material contacts the skin, immediately cool before attempting removal. Wash with soap and water. If symptoms develop and persist, get

medical attention.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious

person. Aspiration may cause pulmonary edema and pneumonitis. Get

medical attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water fog. Foam Small Fires: Dry chemical. Sand. Large fires: Treat as oil fire.

Vermiculite.

Special firefighting procedures: Water spray may be ineffective. Oil will float on water and can spread fire.

Unusual fire or explosion hazards: None

IDH number: 457453

Hazardous combustion products: Oxides of sulfur. Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways. Prevent further leakage or

spillage if safe to do so.

Clean-up methods: Clean-up methods - large spillage. Flush with water. Follow all local, state,

federal and provincial regulations for disposal.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Keep container closed.

Storage: Keep in a cool, well ventilated area.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Zinc oxide	2 mg/m3 TWA Respirable fraction. 10 mg/m3 STEL Respirable fraction.	5 mg/m3 PEL Fume. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Distillates (petroleum), solvent-dewaxed heavy paraffinic	5 mg/m3 TWA Inhalable fraction.	500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
Reinforcing filler	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Alkyl Benzene	None	None	None	None
Filler	6 mg/m3 STEL Inhalable fraction. 2 mg/m3 TWA Inhalable fraction.	None	None	None
Sulfonic Ester	None	None	None	None
Sulfonic Ester	None	None	None	None
Filler	None	None	None	None

Engineering controls: Use only with adequate ventilation. Local exhaust ventilation is recommended

when general ventilation is not sufficient to control airborne contamination

below occupational exposure limits.

Respiratory protection: If personal exposure cannot be controlled below applicable limits by

ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Use of Butyl or Nitrile Rubber gloves is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:Semi-SolidColor:WhiteOdor:Mild, PetroleumOdor threshold:Not available.pH:Not available.

Vapor pressure: < 0.01 mm hg (68 °F (20°C))

Boiling point/range:

Melting point/ range:

Not available.

Not available.

Specific gravity: 0.95 - 1.05 at 25 °C (77°F)

Vapor density: Not available. > 180 °C (> 356°F) Flash point: Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not determined Evaporation rate: Not available. Solubility in water: Negligible Partition coefficient (n-octanol/water): Not determined **VOC** content: 2.89 %; 28.9 g/l Not available. Viscosity: **Decomposition temperature:** Not available.

IDH number: 457453 Product name: LOCTITE LB 8034 SYN. GREASE HIGH PERFORM. known as ViperLube(TM)

Page 3 of 6

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 457453

Oxides of sulfur. Oxides of carbon.

Incompatible materials: Oxidizing agents.

Reactivity: Not available.

Conditions to avoid: None known

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Mist or spray may cause respiratory tract irritation and delayed onset pulmonary edema.

Skin contact: Causes skin irritation.

Eye contact: Causes serious eye damage.

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Zinc oxide	Oral LD50 (RAT) = > 5 g/kg	Blood, Gastrointestinal, Immune system, Irritant, Kidney, Metabolic, Nervous System, Pancreas, Respiratory, Skin	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	None	Irritant	
Reinforcing filler	Oral LD50 (RAT) = 6,450 mg/kg	Nuisance dust	
Alkyl Benzene	None	No Records	
Filler	None	No Records	
Sulfonic Ester	None	No Records	
Sulfonic Ester	None	Eyes, Irritant	
Filler	None	Allergen, Corrosive, Irritant, Kidney	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Zinc oxide	No	No	No
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No	No	No
Reinforcing filler	No	No	No
Alkyl Benzene	No	No	No
Filler	No	No	No
Sulfonic Ester	No	No	No
Sulfonic Ester	No	No	No
Filler	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, solid, n.o.s. (Zinc oxide)

Hazard class or division:

Identification number: UN 3077 Packing group: Ш

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc oxide)

Hazard class or division: Identification number:

UN 3077 Packing group: Ш Marine pollutant: Zinc oxide

Additional information: IMDG-Code: Segregation group 7- Heavy metals and their salts

REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: One or more components of this product are not listed on the U.S. Toxic Substances

Control Act (TSCA) inventory. As such, this product may only be used for research and development purposes as described in 40 CFR 720.36. All other components of this

product are listed or are exempt from listing.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Zinc oxide (CAS# 1314-13-2).

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Lou Fabrizio, Regulatory Affairs Specialist

Issue date: 01/22/2015

Product name: LOCTITE LB 8034 SYN. GREASE HIGH PERFORM. known as ViperLube(TM) IDH number: 457453

Page 5 of 6

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 457453