# MSA Workman® Mini PFL Product Specifications



#### Twin-Leg Carabiner Connection

Keeps harness D-ring available for use with other equipment while climbing, or for rescue purposes

### **Swivel Eye Connection**

Eliminates line twisting

#### **Internal Pawl-Lock**

Provides many lower level tie-off points for numerous work applications

## High Weight Capacity

Accommodates users up to 400 lb. (181 kg)



Performance Specifications		
TENSILE STRENGTH		
US	3,000 lb. (1,361 kg) minimum	
EU	3,372 lb. (1,530 kg) minimum	
MAXIMUM CAPACITY		
US	400 lb. (181 kg)	
EU	310 lb. (141 kg)	
MAXIMUM ARREST DISTANCE	24" (610 mm, US)	
AVERAGE ARREST FORCE	per ANSI Z359.14	
DRY	1350 lb. (612 kg)	
COLD / HOT / WET	1575 lb. (714 kg)	
Approvals		
APPROVALS	ANSI Z359.14, class A; OSHA	

Ordering Information	
10157844 Workman Mini PFL Single-leg with Carabiner	
10157862 Workman Mini PFL Twin-leg with Carabiner	
10157864	Workman Mini PFL Twin-leg with Tie-back™

Material Specifications	
WEIGHT	1.78 lb. (0.8 kg, w/o snaphook)
UNIT LENGTH	13" (330 mm)
UNIT WIDTH	3.93" (100 mm)
UNIT DEPTH	2.12" (54 mm)
UNIT HOUSING	Polycarbonate
LIFELINE MATERIAL	Nylon
LIFELINE LENGTH	
STANDARD	6 ft. (1.8 m)
TIE-BACK	9 ft. (2.7 m)

Note: This Bulletin contains only a general description of the products shown. While product uses and performance capabilities are generally described, the products shall not, under any circumstances, be used by untrained or unqualified individuals. The products shall not be used until the product instructions/user manual, which contains detailed information concerning the proper use and care of the products, including any warnings or cautions, have been thoroughly read and understood. Specifications are subject to change without prior notice.

MSA operates in over 40 countries worldwide. To find an MSA office near you, please visit **MSAsafety.com/offices**.