

## Extended hand protection for light to mid duty work

- **Adhesive-resistant:** The expert design resists tape and adhesives on the job
- **Tactile sensitivity:** Due to its soft and flexible formulation, this thin nitrile glove provides impressive tactile sensitivity for light to mid-duty work
- **Expanded protection:** The extended cuff means the gloves offer additional protection over the wrist and forearm
- **Smart packaging:** Packed with 100 gloves per box, these gloves offer more content per box than most extended-cuff gloves



### Industries

- Food Processing
- Life Sciences
- Healthcare

### Recommended For

- All food processing, applications that have food contact
- Sample taking and processing
- Extra protection over the wrist and arm
- Standard, moderate risk examination procedures
- Protection from Type I latex allergy in HCW's or patients

# TECHNICAL DATA SHEET

| Product Information    |  |
|------------------------|--|
| External Glove Surface | Textured Fingers   |
| Audit Standards        | EN ISO 13485:2012  |
| Packaging Overview     | 100 gloves per dispenser<br>10 dispensers per case<br>1000 gloves per case                               |
| Storage Instructions   | Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition. |
| Country Of Origin      | Malaysia   |
| Product Segmentation   | High Risk  |
| Antistatic             | Not Tested   |

## PHYSICAL PROPERTIES

|   | Typical Values      | Testing Method      |                  |
|---|---------------------|---------------------|------------------|
| Length (mm/inches)                      | 290 / 11.4          | ASTM D3767,EN 420   |                  |
| Freedom from Holes (Inspection level I) | 1.5 AQL             | ASTM D5151,EN 455-1 |                  |
| Palm Thickness (mm/mils)                | 0.10 / 3.9          | ASTM D3767,EN 420   |                  |
| Finger Thickness (mm/mils)              | 0.13 / 5.1          | ASTM D3767,EN 420   |                  |
|   | <b>BEFORE AGING</b> | <b>AFTER AGING</b>  |                  |
| Ultimate Tensile Strength (MPa)         | 33                  | 32                  | ASTM D412 & D573 |
| Elongation at Break (%)                 | ≥ 500               | ≥ 400               | ASTM D412        |
| Force at break (N)                      | 7                   |                     |                  |

## ORDERING INFORMATION

| Size         | XS (5.5 - 6) | S (6.5 - 7) | M (7.5 - 8) | L (8.5 - 9) | XL (9.5 - 10) | XXL (10.5 - 11) | XXXL (11.5 - 12) |
|--------------|--------------|-------------|-------------|-------------|---------------|-----------------|------------------|
| Product Code | USE-880-XS   | USE-880-S   | USE-880-M   | USE-880-L   | USE-880-XL    | USE-880-XXL     | USE-880-XXXL     |

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

### Asia Pacific Region

MY +603 8310 6688  
apac.medical@ansell.com  
CN: +86 21 38275000  
infochina@ansell.com  
JP: +813 5549 8151  
info.medical.jp@ansell.com

### North America Region

Ansell Healthcare Products LLC  
T: +1 800 800 0444  
F: +1 800 800 0445

### Latin America & Caribbean Region

BR +55 (11) 3356-3100  
latam.medical@ansell.com  
MX: +52 442 296 2050  
latam.medical@ansell.com  
CO: +57 1 288 3247  
latam.medical@ansell.com

### Australia

Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578

### Russia

Ansell PYC  
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending; [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2024 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

