



SPECIFICATION SHEET

150-2-14



NOVAX RUBBER INSULATING GLOVES: CLASS 2

- Meet ANSI/ASTM D120 standard and NFPA 70E for use around electrical hazards and arc flash protection.
- Contoured shape reduces hand fatigue.
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability.
- Silicone free.

APPLICATIONS

Used exclusively for electrical purposes, such as power generation, electrical contractors, hybrid automotive repair/service, hybrid automobile manufacturing, industrial plant maintenance, utilities.

MAX USE VOLTAGE

	SC V rms	DC V
CLASS 2	17,000	25,500

10

NOVAX™ by G.B. INDUSTRIES

ANSI / ASTM CLASS 2 MADE IN MALAYSIA D120 TYPE I

MAX USE VOLT 17000V AC



TECHNICAL DATA

SHELL	Natural Rubber
COLOR	■ Black
CUFF STYLE	Rolled
SIZES	8-11
PACKAGING	1 pair per bag/box, 12 pair per case
CASE	16.9" x 16.9" x 19.8"
CASE WEIGHT	19.8 lbs / 9.0 kg
COO	Malaysia

BARCODES

ITEM	PAIR	CASE
■ 150-2-14/8	01616314050915	02616314050914
■ 150-2-14/9	01616314050922	02616314050921
■ 150-2-14/10	01616314050939	02616314050938
■ 150-2-14/11	01616314050946	02616314050945

DIMENSIONS (in/cm)

	8	9	10	11
A	14.0 / 36.0	14.0 / 36.0	14.0 / 36.0	14.0 / 36.0
B	3.9 / 10.0	4.1 / 10.5	4.7 / 12.0	5.3 / 13.5

Max Thickness: 2.29mm*

