




# SPECIFICATION SHEET

## 120-4600



### VIZ™ BY MAXIMUM SAFETY®

- Synthetic leather palm enhances grip in dry and light oil applications while providing dexterity
- PVC grip on index finger and thumb for fine parts handling
- Reinforced thumb crotch for extended glove life, enhanced comfort, increased abrasion resistance and added durability in a high-wear area
- Spandex fabric back for comfort and breathability
- Elastic wrist for easy on/off
- Lycra fabric fourchettes enhance the natural contour of the glove
- Hi-Vis coloring and reflective binding makes this product very easy to see in low-light applications
- Launderable for extended life and to reduce replacement costs
- Retail Ready

### APPLICATIONS

- Light Construction
- Auto Repair
- Demolition
- Manufacturing
- Fabrication
- Landscaping

### CARE INSTRUCTIONS

Machine wash in cold water. Do not bleach. Hang dry; tumble dry is not recommended. Do not iron.

### TECHNICAL DATA

MATERIAL	Spandex / Nylon / Polyester / Polyurethane / Lycra
CONSTRUCTION	<b>Back:</b> Unlined spandex fabric (96% nylon, 4% spandex) <b>Palm:</b> Synthetic leather (60% nylon, 40% polyurethane), 0.8mm gauge <b>Fingers:</b> Heavy lycra fabric (94% nylon, 6% lycra)
COLOR	■ Orange / ■ Black
CUFF STYLE	Open cuff, elastic wrist
SIZES	S - XXL
PACKAGING	12 pairs per dozen, 6 dozen per case
CASE	19.7" x 15" x 13.4" / 46cm x 36cm x 31cm
CASE WEIGHT	11 lbs / 5g
COO	Pakistan

### PERFORMANCE PROPERTIES

EN388: 2121						
ABRASION	0	1	2	3	4	-
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-

### BARCODES

ITEM	PAIR	DOZEN	CASE
120-4600/S	616314069529	01616314069528	02616314069527
120-4600/M	616314069512	01616314069511	02616314069510
120-4600/L	616314069505	01616314069504	02616314069503
120-4600/XL	616314069536	01616314069535	02616314069534
120-4600/XXL	616314069543	01616314069542	02616314069541



### DIMENSIONS (in/cm)

	S	M	L	XL	XXL
<b>A</b>	8.1 / 20.6	8.5 / 21.6	8.9 / 22.6	9.3 / 23.6	9.5 / 24.1
<b>B</b>	3.75 / 9.5	4 / 10.2	4.25 / 10.8	4.5 / 11.4	4.75 / 12.1

Tolerance (in): +/- 0.125

