

3M Hearing Solutions

3M™ PELTOR™ HearPlugs Listen-Only Communication



- ► Hearing protection
- Clear sound reproduction with a noise reduction rating from a NVLAP-accredited lab
- ► Listen-only communication
- Improved ability to hear communication in high-noise environments
- Helps to reduce repeated or missed messages caused by inability to clearly understand transmissions
- ► Compact, low weight design



3M Personal Safety Division 3M Center, Building 235-2NW-70 St. Paul, MN 55144-1000 3M.com/Hearing For More Information Technical Service

Technical Service Customer Service 70-0716-7188-0 1-800-243-4630 1-800-328-1667

3M™ PELTOR™ HearPlug Kits

Product Number	Product Description	3M™ Stock Number				
HTM26	3M™ PELTOR™ HearPlug - 3.5mm mono	70-0716-7567-5				
HTM26-02	3M™ PELTOR™ HearPlug - 3.5mm mono curly cable	70-0716-7568-3				
HTM27	3M™ PELTOR™ HearPlug - 2.5mm mono	70-0716-7569-1				
HTM27-02	3M™ PELTOR™ HearPlug - 2.5mm mono curly cable	70-0716-7570-9				
HTM28	3M™ PELTOR™ HearPlug - 3.5mm threaded stereo	70-0716-7571-7				

3M™ PELTOR™ HearPlug Ear Tips Replacements

Product Number	Product Description	3M™ Stock Number				
PELTIP1	3M™ E-A-R™ UltraFit™ Reusable comm. ear tips - 25 Pairs	70-0715-2260-4				
PELTIP6	3M™ E-A-R™ Classic™ Disposable comm. ear tips - 100 Pairs	70-0716-7572-5				

Laboratory Attenuation ANSI S3.19-1974

3M™ E-A-R™ Classic™ Disposable Communication Ear Tip (PELTIP6) used with 3M™ PELTOR™ HearPlug

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR	CSA Class
Mean Attenuation (dB)	32.2	39.3	39.2	41.9	38.6	42.6	43.7	47.7	45.7	- 30 db	AL
Standard Deviation (dB)	6.5	6.0	5.1	4.6	2.9	3.3	3.0	5.0	4.4		

3M™ E-A-R™ UltraFit™ Reusable Communication Ear Tip (PELTIP1) used with 3M™ PELTOR™ HearPlug

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR	CSA Class
Mean Attenuation (dB)	32.9	32.0	32.1	32.8	33.9	36.5	34.6	34.2	36.8	- 24 db	AL
Standard Deviation (dB)	6.2	4.9	4.0	3.6	4.3	4.3	5.0	4.1	3.8		

* Research suggests that many users will receive less noise reduction than indicated by the NRR due to factors including variation in earplug fit, and earplug fitting skill and motivation of the user. 3M recommends fit testing of hearing protectors. If the NRR is used to estimate typical workplace protection, 3M recommends that the NRR be reduced by 50% or in accordance with applicable regulations.

Speaker microphone with audio jack is not included, purchased separately.

Available in three choices of plug sizes: 2.5mm, 3.5mm, 3.5mm threaded.

Easy-to-insert communication eartip allows radio transmissions to pass through & be heard clearly.

Coil allows for head movement and placement.

Soft, acoustic tube comfortably wraps around behind the ear for a snug fit. -



3M Personal Safety Division products are for occupational use only.

© 3M 2016. All rights reserved. 3M and E-A-R are trademarks of 3M Company, used under license in Canada.

PELTOR is a trademark of 3M Svenska AB, used under license in Canada.