#### **RATCHETING CHAIN WRENCHES**

Special head design allows you to turn wrench in either direction. Ratcheting action makes it possible to re-grip without removal. For parts of most any size and shape.

**No. 7400** – Chain wrench, cap. <sup>1</sup>/<sub>2</sub>" to 4<sup>3</sup>/<sub>4</sub>" O.D. (Capacity= 333 ft. lbs.) Wt., 2.0 lbs.

**No. 7401** – Chain wrench, cap. 3" to 6<sup>3</sup>/<sub>4</sub>" O.D. (Capacity= 666 ft. lbs.) Wt., 5 lbs.

**No. 209199** – Replacement chain with pin for No. 7400 chain wrench (16" long).

**No. 209200** – Replacement chain with pin for No. 7401 chain wrench (24" long).

#### ADJUSTABLE HOOK SPANNER WRENCH

Needed wherever turret adjusting nuts or packing gland nuts are used. Cap.: 11/2" to 4". Handle overall length: 19".

**No. 885** – Adjustable hook spanner wrench. Wt., 3.0 lbs.

### ADJUSTABLE HOOK SPANNER WRENCH

Replace many fixed-size wrenches... cover range of capacities needed to service industrial tractors and other equipment. Drop-forged jaws adjust to eleven positions for a capacity of 43/4" to 123/4" O.D. Handle overall length: 24"; diameter: 1".

**No. 7307** – Spanner wrench with one <sup>3</sup>/8" thick jaw. Wt., 7.3 lbs.

**No. 7308** – Spanner wrench with two interchangeable jaws: one <sup>3</sup>/<sub>8</sub>" thick, one <sup>3</sup>/<sub>4</sub>" thick. Wt., 11.0 lbs.

# **HEAVY-DUTY ADJUSTABLE SPANNER**

Extra heavy construction. Has one <sup>3</sup>/<sub>4</sub>" thick, eleven-position hook-jaw for a capacity of 4<sup>3</sup>/<sub>4</sub>" to 12<sup>3</sup>/<sub>4</sub>" O.D. Drop-forged. Handle length: 25<sup>3</sup>/<sub>4</sub>"; handle dia.: 1<sup>5</sup>/<sub>16</sub>".

**No. 7309** – Heavy duty adjustable hook spanner wrench. Wt., 13.3 lbs.

### **ADJUSTABLE GLAND NUT WRENCH**

Designed to handle 2" to 6" dia. hydraulic cylinder gland nuts on many construction vehicles. Fits 1/4" and 5/16" dia. pin holes; features a 3/4" sq. drive.

**No. 1266** – Adjustable gland nut wrench. Wt., 3.0 lbs.

**No. 204928** – Replacement pin for No. 1266

#### **PRY BARS**

Our rolling head pry bars are an extremely popular and useful tool. Head may be used for almost any prying job since a great deal of leverage can be obtained. Long tapered body may be used as a lining-up drift.

**No. 7162** – Pry bar; <sup>3</sup>/8" round, 6" long. Wt., 0.3 lb.

**No. 7163** – Pry bar; <sup>7</sup>/<sub>16</sub>" round, 12" long. Wt., 0.6 lb.

**No. 7164** – Pry bar; <sup>9</sup>/<sub>16</sub>" round, 16" long. Wt., 1.1 lbs.

**No. 7165** – Pry bar; 3/4" round, 18" long. Wt., 2.2 lbs.

### **JIMMY BARS**

Ideal for general lifting or prying. Heat treated chrome alloy steel to resist bending or breaking.

**No. 7166** – Jimmy bar; <sup>5</sup>/<sub>8</sub>" round, 18" long. Wt., 1.4 lbs.

**No. 7167** – Jimmy bar; <sup>3</sup>/<sub>4</sub>" round, 24" long. Wt., 2.5 lbs.

**No. 7168** – Jimmy bar; <sup>7</sup>/8" round, 30" long. Wt., 4.3 lbs.

# "MAJOR PERSUADER" JIMMY BARS

Two big jimmy bars for big jobs. Forged from chrome alloy steel.

**No. 7420** – Jimmy bar; <sup>7</sup>/<sub>8</sub>" round, 46" long. Wt., 7.5 lbs.

**No. 7421** – Jimmy bar; 1" round, 54" long. Wt., 11.3 lbs.

# WRENCHES, PRY BARS

Spanners & Jimmy Bars





7166 7167 7168 7420 7421