

BOTTLE JACKS

2-110 Ton

Portable Hydraulic Power



INDUSTRIAL LIFTING AND PUSHING APPLICATIONS.

- Choose from this complete line of premium quality, standard bottle jacks. Ideal for use in any number of industrial lifting and pushing applications.
- The 9110B, 9015B, 9022B and 9033B feature a beveled base which allows the jack to “follow” the load, reducing the chance of dangerous side-loading.
- Many jacks feature screw extensions.
- All jacks can be used in the vertical, angled or horizontal positions.
- Serrated or contoured saddles help stabilize the load for a safer lift.
- All jacks meet ASME B30.1 standards and carry the Power Team Powerthon™ Lifetime Warranty.
- 110-ton jack features dual pumps for time-saving two-speed operation.

ORDERING INFORMATION*

Cap. Tons	Stroke (in.)	Order Number	Retracted Height (in.)	Length of Screw (in.)	Height w/Screw Ext. (in.)	No. Pump Strokes to Ext. Piston (in.)	Saddle Dia. (in.)	Base Size (in.)	Pump Handle Length (in.)	Handle Effort at Rated Cap. (lbs.)	Carry Handle	Product Weight (lbs.)
2	4½	9002A	7⅞	1⅞	13⅞	5	1	4⅞ x 2⅞	12¼	75	No	4.8
3	4½	9003A	7½	2⅞	14⅞	10	1⅞	4½ x 2⅞	19¼	45	No	5.8
5	4¾	9005A	7⅞	2¾	15⅞	12	1⅞	5⅞ x 3	21⅞	55	No	8
8	4¾	9008A	7⅞	2¾	15⅞	18	1½	6 x 3½	23⅞	75	No	12.1
12	5⅞	9112A	9½	3⅞	18½	26	1⅞	6½ x 4⅞	23⅞	60	Yes	17.5
15	6⅞	9015B	9⅞	4½	19⅞	27	2⅞	5⅞ x 5½†	27⅞	90	No	18.3
20	6¼	9120A	10⅞	3⅞	20½	22	2	7⅞ x 5⅞	31½	70	Yes	28.5
22	6⅞	9022B	9⅞	4⅞	20½	36	2⅞	6½ x 6⅞†	27⅞	90	Yes	23.6
30	6¼	9030A	11	—	17¼	35	2⅞	7⅞ x 5⅞	39⅞	50	Yes	41.2
33	5⅞	9033B	9⅞	4⅞	19¼	56	2⅞	7¼ x 6⅞†	27⅞	88	Yes	32
50	6¾	9050A	12	—	18¼	35	3	9⅞ x 7⅞	39⅞	85	Yes	78
110	6⅞	9110B	11⅞	—	17⅞	40/160‡	4⅞	13⅞ x 11⅞	27⅞	79	Yes	154.3

*See current price list for shipping weights.

† Comes with a Beveled Base.

‡ 2 Speed: Rapid advance≈40 strokes; Lift mode≈160 strokes.