

EXETER®

Sporty style with maximum protection



Glossy Black Frame

Part	Lens
SB5110DT •••	Clear Anti-Fog
SB5120DT ••••	Gray Anti-Fog
SB5133DT ••	Shooter's Amber Anti-Fog
SB5155DT •••	Sky Red Mirror Anti-Fog
SB5170DT •••	Silver Mirror Anti-Fog
SB5175DT ••	Blue Mirror Anti-Fog
SB5180DT •	Indoor/Outdoor Mirror Anti-Fog

Charcoal Gray Frame

Part	Lens
SCG5110DT •••	Clear Anti-Fog
SCG5120DT ••••	Gray Anti-Fog

- Sporty style with maximum protection.
- Curved lens with side window gives fashionable look with panoramic view.
- Durable frame gives a pressure free fit.
- Soft nose piece and rubber insert temple tips provide a comfortable fit.
- Scratch resistant lenses filter out 99.9% of harmful UV rays.

GENERAL SPECIFICATION

Bridge: 13.4mm
Closest Point Between Lens: 14.8mm
Closest Point Between Temple Tips: 93mm
Lens Base: 8 Curve
Lens Size Diagonal: 70.8mm
Lens Size Vertical: 44mm
Lens Thickness: 2.30mm
Overall Length (Lens-Tip): 157mm
Overall Width (Hinge-Hinge): 127.5mm
PD: 68mm
Weight: 29gm










PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Outer Carton: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base curve, wrap around design with side protection
Side Window Lens	Polycarbonate	Along with the front lens makes full wrap around image
Frame	Nylon	Durable & flexible, sporty style
Nose Piece	PVC	Universal
Temple	Nylon	Spatula
Temple Tip	PVC	Comfortable & good for color variants
Hinge	Nylon	3 barrel type, integral to frame & temples
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB5110DT	 Clear Anti-Fog	P Z87 + U6	P Z87 +
SB5120DT	 Gray Anti-Fog	P Z87 + U6 L2.5	P Z87 +
SB5133DT	 Shooter's Amber Anti-Fog	P Z87 + S	P Z87 +
SB5155DT	 Sky Red Mirror Anti-Fog	P Z87 + S	P Z87 +
SB5170DT	 Silver Mirror Anti-Fog	P Z87 + S	P Z87 +
SB5175DT	 Blue Mirror Anti-Fog	P Z87 + S	P Z87 +
SB5180DT	 Indoor/Outdoor Mirror Anti-Fog	P Z87 + S	P Z87 +
SCG5110DT	 Clear Anti-Fog	P Z87 + U6	P Z87 +
SCG5120DT	 Gray Anti-Fog	P Z87 + U6 L2.5	P Z87 +

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact