



**PYRAMEX**  
Perform At Your Peak

Emerge Plus / GL102



**Emerge® Plus** ANSI • CSA •



RUBBER TIPS



RUBBER NOSEPIECE

Rubber temple tips // Soft nosepiece provides comfort for extended use

**Full Readers**

**Translucent Gray Frame | 7 Variations**

SG9810R15 ••	Clear	+1.5 Mag
SG9810R20 ••	Clear	+2.0 Mag
SG9810R25 ••	Clear	+2.5 Mag
SG9810R30 ••	Clear	+3.0 Mag
SG9820R15 ••	Gray	+1.5 Mag
SG9820R20 ••	Gray	+2.0 Mag
SG9820R25 ••	Gray	+2.5 Mag

**Top Insert Readers**

**Translucent Gray Frame | 3 Variations**

SG9810TR15 ••	Clear	+1.5 Mag
SG9810TR20 ••	Clear	+2.0 Mag
SG9810TR25 ••	Clear	+2.5 Mag

**i** The top insert reader for the Emerge Plus is strategically placed for applications in which user is frequently looking up.

**There's more to see at**  
**PYRAMEXSAFETY.COM**

(P) 800.736.8673 | (F) 901.861.4967

ANSI Z87.1+ standards (•) | Canadian CSA Z94.3-15 & third-party certification (••)  
For specific lens options visit our website or contact your sales representative.

## Emerge® Plus

### General Specifications

Weight: 31.3 gm  
 Bridge: 10.6 mm  
 Lens base: 6 curve  
 Lens size diagonal: 54.6 mm  
 Lens size vertical: 42.5 mm  
 Lens thickness: 2.2 mm  
 Overall length (lens - tip): 160 mm  
 Overall width (hinge - hinge): 129 mm  
 Closest point between temple tips: 88 mm

### Materials

Lens: polycarbonate  
 Frame: nylon  
 Temples: polycarbonate  
 Temple tips: thermoplastic rubbers (TPR)  
 Hinge: polycarbonate  
 Screw: stainless steel  
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Frame Marking	Temple Marking
SG9810R15	P Z87 + U6	+1.50	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810R20	P Z87 + U6	+2.00	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810R25	P Z87 + U6	+2.50	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810R30	P Z87 + U6	+3.00	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9820R15	P Z87 + U6 L2.5	+1.50	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9820R20	P Z87 + U6 L2.5	+2.00	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9820R25	P Z87 + U6 L2.5	+2.50	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810TR15	P Z87 + U6	+1.50	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810TR20	P Z87 + U6	+2.00	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810TR25	P Z87 + U6	+2.50	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 UV Filter Transmittance  
 U6: .01% max effective far UV • .1% max near UV  
 Visible Light Filters  
 L2.5: 29% max visible light

### Frame Marking Symbols

+1.50: magnification of +1.5  
 +2.00: magnification of +2.0  
 +2.50: magnification of +2.5  
 +3.00: magnification of +3.0

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 - 2: Rx  
 +: High impact  
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



# Emerge® Plus

## General Specifications

Weight: 31.3 gm  
Bridge: 10.6 mm  
Lens base: 6 curve  
Lens size diagonal: 54.6 mm  
Lens size vertical: 42.5 mm  
Lens thickness: 2.2 mm  
Overall length (lens - tip): 160 mm  
Overall width (hinge - hinge): 129 mm  
Closest point between temple tips: 88 mm

## Materials

Lens: polycarbonate  
Frame: nylon  
Temples: polycarbonate  
Temple tips: thermoplastic rubbers (TPR)  
Hinge: polycarbonate  
Screw: stainless steel  
Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Frame Marking	Temple Marking
SG9810R15	P Z87 + U6	+1.50	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810R20	P Z87 + U6	+2.00	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810R25	P Z87 + U6	+2.50	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810R30	P Z87 + U6	+3.00	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810TR15	P Z87 + U6	+1.50	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810TR20	P Z87 + U6	+2.00	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15
SG9810TR25	P Z87 + U6	+2.50	P Z87 - 2 + / P c SEI CAN/CSA Z94.3-15

## Lens Marking Symbols

P: Manufacturer's mark  
Z87: ANSI standard for eye and face protection devices  
+: High impact

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

## Temple Marking Symbols

P: Manufacturer's mark  
Z87: ANSI standard for eye and face protection devices  
- 2: Rx  
+: High impact  
c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

## Frame Marking Symbols

+1.50: magnification of +1.5  
+2.00: magnification of +2.0  
+2.50: magnification of +2.5  
+3.00: magnification of +3.0

