




FR Protection

Intended to be worn over primary FR apparel to protect it from grease, dirt and non-toxic liquids, in order to extend the life of the primary FR.


Passes ASTM D6413 vertical flame resistance test. Breathable fabric chars—no flame or molten drip. Recommended applications include turnarounds, oil & gas, manufacturing, and industrial.

Available Garments




Coverall with Elastic Wrists and Open Ankles

#9012
Size: Medium- 4XL
25 per case



Coverall with Attached Hood, Elastic Wrists and Ankle

#9015
Size: Medium- 4XL
25 per case



Coverall with Attached Hood and Boots, Elastic Wrists

#9019
Size: Medium- 4XL
25 per case

PyroGuard FR®

TEST CONDUCTED	TEST METHOD	RESULTS
Grab / Tensile - Machine Direction	ASTM D5034-2001	34 lbs.
Grab / Tensile- Cross Direction	ASTM D5034-2001	26 lbs.
Vertical Flammability - Machine Direction	ASTM D6413	Pass
Vertical Flammability - Cross Direction	ASTM D6413	Pass
Electrostatic Decay Rate	ASTM D257	Pass



- Phosphate-based fire retardant deprives flames of their fuel source
- High moisture vapor transmission rate (MVTR) helps wearers feel cooler
- Elastic back stretches with user for more comfort and better tear resistance
- Storm flap over zipper adds an extra layer of protection
- Passes ASTM D6413 Vertical Flame Testing
- Meets NFPA 2113 requirement for section 5.1.9