



HAMMER SELECTION GUIDE

HAMMERS	Handle	Unique Feature	Type			Face		Weight Ounces					
			Framing	Rip	Curve	Checkered	Smooth	7	13	16	20	22	24
FatMax® Large Strike Face AntiVibe®	One-Piece Steel	75% Larger Strike Face	X	X	X	X	X			X	X	X	
FatMax® Graphite	Jacketed Graphite	Increased Durability versus Previous Model	X	X		X						X	
FatMax® Overstrike	Hickory	Overstrike	X	X		X						X	
FatMax® Hickory	Hickory	Magnetic Nail Starter	X	X		X						X	
FatMax® AntiVibe®	One-Piece Steel	Tuning Fork	X	X	X	X	X			X	X	X	X
One-Piece Steel	One-Piece Steel	—		X	X		X			X	X		
Jacketed Graphite	Jacketed Graphite	—		X	X		X			X	X		
Jacketed Fiberglass	Jacketed Fiberglass	Absorbs Vibrations		X	X		X	X		X	X		
Wood	Wood	—		X	X		X	X	X	X			

Type	Description
Framing Hammers	Used for Framing and Heavy-Duty Construction
Rip Claw Hammers	Used for Heavy-Duty Carpentry
Curve Claw Hammers	Used for Light-Duty Carpentry

SPECIALTY HAMMERS	Description	Handle				
		AntiVibe®	Jacketed Graphite	Jacketed Fiberglass	Hickory	Compo-Cast®
Ball Pein	Striking chisels and punches, riveting and shaping or bending metal	X	X		X	X
Engineer	Striking wood, metal or stone	X		X	X	X
Blacksmith	Striking unhardened metals	X		X	X	X
Drilling	Striking chisels and punches, star drills and unhardened nails in confined spaces	X		X	X	X
Drywall	Installing drywall or gypsum board	X				
Brick	Cutting/setting brick, stone and masonry	X			X	X
Carpenter's	Cutting/splitting wood, driving stakes and unhardened nails	X				
Shingler's	Installing shingles and other roofing material	X				
Tack	Holding and driving tacks and brads				X	X
Soft Face	Soft face helps minimize marring and surface damage				X	X
Rubber Mallet	Rubber head face helps minimize marring and surface damage				X	X
Compo-Cast®	Dead blow function eliminates bounceback when striking hardened surface and helps prevent marring					X



STANLEY® FATMAX® LARGE STRIKE FACE ANTIVIBE® HAMMERS



- 75% larger* strike face for improved striking accuracy.
- AntiVibe® technology minimizes vibration and shock at impact.
- Torsion control stabilizers reduce arm-twisting fatigue.
- Magnetic Nail Start feature for extended reach for one-handed nailing.
- Exclusive rim temper reduces incidences of chipping or spalling.
- Forged, one-piece steel construction for strength and durability.
- Slip-resistant handle for a secure grip and comfort
- Precision balanced.

*Than traditional hammers.



Product #	Type	Head Weight	Claw	Face	Head Length	Face Diameter	Length
51-162	Nailing	16 oz (454 g)	Curve	Smooth	5-1/2 in (140 mm)	1-1/2 in (38 mm)	13-1/8 in (333 mm)
51-163	Nailing	16 oz (454 g)	Rip	Smooth	5-1/2 in (140 mm)	1-1/2 in (38 mm)	13-1/8 in (333 mm)
51-165	Nailing	20 oz (567 g)	Rip	Smooth	5-3/4 in (146 mm)	1-19/32 in (41 mm)	13-3/4 in (350 mm)
51-167	Framing	22 oz (624 g)	Rip	Checkered	6 in (152 mm)	1-3/4 in (44 mm)	16 in (406 mm)
51-177	Framing	22 oz (624 g)	Rip	Smooth	6-1/8 in (155 mm)	1-1/2 in (38 mm)	16 in (406 mm)

STANLEY® FATMAX® ANTIVIBE® CHECKERED FRAMING HAMMER



- Patented torsion control grip technology reduces the effects of torque on wrists and elbows.
- Patented AntiVibe® technology minimizes vibration and shock at impact.
- Magnetic Nail Start feature for extended reach and one-handed nailing capability.
- Forged, one-piece steel construction for increased strength and durability.



Product #	Head Weight	Claw	Face Diameter	Overall Length
51-215	24 oz (680 g)	Rip	1-1/4 in (31 mm)	16 in

STANLEY® FATMAX® ANTIVIBE® HAMMERS



- Forged, one-piece steel construction for increased strength and durability.
- Patented tuning fork design helps reduce harmful vibration that can cause wrist and arm injuries.
- Rim tempered face reduces incidences of chipping or spalling.
- Molded, textured rubber grip to increase comfort and performance.
- Flared end on grip helps to prevent hammer from slipping out of user's hand (Nailing hammers only).



Product #	Head Weight	Claw	Face	Head Length	Face Diameter	Overall Length
51-941	16 oz (454 g)	Curve	Smooth	5-1/8 in (130 mm)	1-1/2 in (38 mm)	13-5/16 in (338 mm)
51-942	16 oz (454 g)	Rip	Smooth	5-5/16 in (135 mm)	1-3/16 in (30 mm)	13-7/16 in (342 mm)
51-943	20 oz (567 g)	Curve	Smooth	5-1/8 in (130 mm)	1-7/8 in (48 mm)	14 in (355 mm)
51-944	20 oz (567 g)	Rip	Smooth	5-3/4 in (146 mm)	1-7/8 in (48 mm)	13-5/16 in (338 mm)
51-946	22 oz (624 g)	Rip	Smooth	5-3/4 in (146 mm)	1-3/8 in (35 mm)	15-3/4 in (400 mm)
51-947	22 oz (624 g)	Rip	Checkered	5-3/4 in (146 mm)	1-3/8 in (35 mm)	15-3/4 in (400 mm)





STANLEY® FATMAX® GRAPHITE FRAMING HAMMERS



- Jacketed graphite core adds strength and durability in the handle while providing the “feel of wood”.
- Forged and heat-treated head for durability.
- Rim temper reduces incidence of chipping or spalling.
- Flared head design provides a large strike surface for optimal nail-driving performance.
- Magnetic Nail Start feature for extended reach for one-handed nailing.
- Checkered face design increases control and accuracy when driving nails.



Magnetic Nail Starter for One-Handed Nailing

Product #	Head Weight	Claw	Head Length	Face Diameter	Overall Length	Handle
51-000	22 oz (624 g)	Rip	6-1/4 in (159 mm)	1-1/2 in (38 mm)	17-7/8 in (454 mm)	Straight
51-021	22 oz (624 g)	Rip	6-1/2 in (165 mm)	1-1/2 in (38 mm)	18-1/2 in (470 mm)	Axe

STANLEY® FATMAX® HICKORY HANDLE OVERSTRIKE HAMMER



- Forged and heat-treated head for increased durability.
- Traditional, high-quality hickory handle framing hammer.
- Rim temper reduces incidences of chipping or spalling.
- Magnetic Nail Start feature for extended reach for one-handed nailing.
- Flared head design provides a large striking face for optimal nail-driving performance.
- Long handle for extended reach.
- Checkered face design increases control and accuracy when driving nails.
- Double wedge head-to-handle assembly for extremely secure fit.
- Overstrike steel protection plate helps prevent handle damage.



Overstrike Steel Protection Plate



Magnetic Nail Starter for One-Handed Nailing

Product #	Head Weight	Claw	Head Length	Face Diameter	Overall Length	Handle
51-403	22 oz (624 g)	Rip	6-1/4 in (159 mm)	1-17/32 in (39 mm)	18-5/16 in (464 mm)	Axe

STANLEY® FATMAX® HICKORY HANDLE HAMMER



- Traditional, high-quality hickory handle framing hammer.
- Forged and heat-treated head for durability.
- Rim temper reduces incidences of chipping or spalling.
- Magnetic Nail Start feature for extended reach for one-handed nailing.
- Flared head design provides a large striking face for optimal nail-driving performance.
- Long handle for extended reach.
- Checkered face design increases control and accuracy when driving nails.
- Double wedge head-to-handle assembly for extremely secure fit.



Magnetic Nail Starter for One-Handed Nailing

Product #	Head Weight	Claw	Head Length	Face Diameter	Overall Length	Handle
51-402	22 oz (624 g)	Rip	6-1/8 in (155 mm)	1-1/2 in (38 mm)	18-1/4 in (463 mm)	Axe



STANLEY® STEELMASTER™ NAILING HAMMER

- Heat-treated, high-carbon steel head for improved durability.
- Rim temper reduces incidences of chipping or spalling.
- Fully polished head is laser-marked with hammer weight.
- Steel shaft is chromed and shot-blasted to resist rust.
- Rubber grip is textured to provide comfort and control.
- Flared grip end helps to prevent hammer from slipping out of user's hand.



Product #	Head Weight	Claw	Head Length	Face Diameter	Overall Length
51-031	16 oz (454 g)	Curve	4-7/8 in	1-3/16 in	13-3/8 in

STANLEY® ONE-PIECE STEEL NAILING HAMMERS

- Forged, one-piece steel construction for strength and durability.
- Exclusive rim temper reduces incidences of chipping or spalling.
- Slip-resistant handle for a secure grip and comfort.
- Precision balanced.



Product #	Head Weight	Claw	Face	Head Length	Face Diameter	Overall Length
51-126	16 oz (454 g)	Curve	Smooth	5-5/16 in (135 mm)	1-1/8 in (30 mm)	13-1/8 in (333 mm)
51-127	16 oz (454 g)	Rip	Smooth	5-3/4 in (146 mm)	1-3/16 in (30 mm)	13 in (330 mm)
51-129	20 oz (567 g)	Rip	Smooth	5-3/4 in (146 mm)	1-1/4 in (32 mm)	14 in (355 mm)

STANLEY® FATMAX® JACKETED GRAPHITE NAILING HAMMERS



- 70% larger strike face* for improved striking accuracy.
- Jacketed graphite core adds strength and durability in the handle, reduces vibrations and provides the "feel of wood".
- Overstrike protection helps prevent damage to the handle.
- Exclusive rim temper reduces incidences of chipping or spalling.
- Ergonomic comfort grip features a ribbed surface and flared end to provide a firm grip and help reduce slippage.

*Than traditional hammers.



Product #	Head Weight	Claw	Face	Head Length	Face Diameter	Overall Length
51-505	16 oz (454 g)	Curve	Smooth	4-7/8 in (121 mm)	1-1/2 in (38 mm)	12-7/8 in (327 mm)
51-508	20 oz (567 g)	Rip	Smooth	5-1/2 in (140 mm)	1-5/8 in (41 mm)	13 in (330 mm)



STANLEY® GRAY FIBERGLASS NAILING HAMMERS

- Fiberglass core adds strength and durability in the handle, reduces vibrations and provides the “feel of wood”.
- Exclusive rim temper reduces incidences of chipping or spalling.
- Ergonomic comfort grip features a ribbed surface and flared end to provide a firm grip and help reduce slippage.



Product #	Head Weight	Claw	Face	Head Length	Face Diameter	Overall Length
51-625	16 oz (454 g)	Curve	Smooth	5-1/2 in (140 mm)	1-3/16 in (31 mm)	12-7/8 in (327 mm)
51-627	20 oz (567 g)	Rip	Smooth	6 in (152 mm)	1-3/16 in (31 mm)	12-7/8 in (327 mm)

STANLEY® FIBERGLASS NAILING HAMMERS

- Forged and heat-treated head for increased durability.
- Fully polished head.
- Jacketed, hi-visibility yellow fiberglass handle adds strength and durability.
- Patented head-to-handle assembly.
- Rim tempered face reduces incidences of chipping or spalling.
- Molded, textured rubber grip to increase comfort and performance.



Product #	Head Weight	Claw	Face	Head Length	Face Diameter	Overall Length
51-112	7 oz (198 g)	Curve	Smooth	4 in (101 mm)	29/32 in (23 mm)	11-1/16 in (282 mm)
51-518	16 oz (454 g)	Rip	Smooth	5-1/2 in (140 mm)	1-1/8 in (29 mm)	12-15/16 in (328 mm)
51-621	16 oz (454 g)	Curve	Smooth	5-1/4 in (133 mm)	1-3/16 in (30 mm)	13 in (330 mm)
51-622	16 oz (454 g)	Rip	Smooth	5-5/8 in (143 mm)	1-1/8 in (29 mm)	12-7/8 in (327 mm)
51-624	20 oz (567 g)	Rip	Smooth	6-1/16 in (154 mm)	1-6/32 in (32 mm)	13 in (330 mm)

STANLEY® HICKORY HANDLE NAILING HAMMERS

- Forged high-carbon steel and heat-treated head for increased durability.
- Gray polished head
- Hardwood handle is lightweight and absorbs vibrations.
- Double wedge head-to-handle assembly for extremely secure fit.
- Rim tempered face reduces incidences of chipping or spalling.



Product #	Head Weight	Claw	Face	Head Length	Face Diameter	Overall Length
51-106	13 oz (369 g)	Curve	Smooth	5-1/8 in (131 mm)	1-1/32 in (26 mm)	12-5/16 in (312 mm)
51-613	7 oz (198 g)	Curve	Smooth	4-3/8 in (111 mm)	29/32 in (23 mm)	11-1/4 in (286 mm)
51-713	13 oz (369 g)	Curve	Smooth	5-1/8 in (131 mm)	1-3/32 in (28 mm)	13-7/16 in (342 mm)
51-616	16 oz (454 g)	Curve	Smooth	5-1/4 in (133 mm)	1-3/16 in (31 mm)	13-1/4 in (337 mm)
51-716	16 oz (454 g)	Rip	Smooth	5-5/8 in (143 mm)	1-1/8 in (29 mm)	12-3/4 in (324 mm)



STANLEY® FATMAX® ANTIVIBE® BALL PEIN HAMMERS



- Forged, one-piece steel construction for increased strength and durability.
- Patented tuning fork design helps reduce harmful vibration that can cause wrist and arm injuries.
- Rim tempered face reduces incidences of chipping or spalling.



Product #	Head Weight	Head Length	Face Diameter	Ball Pein Diameter	Overall Length
54-146	16 oz (454 g)	4 in (102 mm)	1-5/16 in (33 mm)	1-1/4 in (32 mm)	13 in (330 mm)
54-148	32 oz (907 g)	4-13/16 in (122 mm)	1-9/16 in (40 mm)	1-3/8 in (35 mm)	15 in (381 mm)

STANLEY® JACKETED GRAPHITE BALL PEIN HAMMERS

- Forged and heat-treated head for increased durability.
- Jacketed graphite handle adds strength and durability, while minimizing shock.



Product #	Head Weight	Head Length	Face Diameter	Ball Pein Diameter	Overall Length
54-708	8 oz (227 g)	3-3/8 in (86 mm)	1-1/16 in (27 mm)	57/64 in (23 mm)	11-5/8 in (295 mm)
54-712	12 oz (340 g)	3-3/4 in (95 mm)	1-11/64 in (30 mm)	15/16 in (24 mm)	11-7/8 in (302 mm)
54-716	16 oz (454 g)	4-1/8 in (105 mm)	1-1/4 in (32 mm)	1 in (25 mm)	12-7/8 in (327 mm)
54-724	24 oz (680 g)	4-3/4 in (121 mm)	1-7/16 in (37 mm)	1-3/16 in (30 mm)	15 in (381 mm)
54-732	32 oz (907 g)	5 in (127 mm)	1-11/16 in (43 mm)	1-13/32 in (36 mm)	15 in (381 mm)

STANLEY® HICKORY HANDLE BALL PEIN HAMMERS

- High-quality hickory handle.
- Forged high-carbon steel head for durability.
- Black hardwood handle is lightweight and absorbs vibrations.
- Rim tempered face reduces incidences of chipping or spalling.



Product #	Head Weight	Head Length	Face Diameter	Ball Pein Diameter	Overall Length
54-004	4 oz (113 g)	2-5/8 in (67 mm)	7/8 in (22 mm)	5/8 in (16 mm)	10-15/16 in (278 mm)
54-008	8 oz (227 g)	3-3/8 in (86 mm)	1-5/64 in (27 mm)	57/64 in (23 mm)	12-3/8 in (314 mm)
54-012	12 oz (340 g)	3-11/16 in (99 mm)	1-3/16 in (30 mm)	7/8 in (22 mm)	13-1/4 in (337 mm)
54-016	16 oz (454 g)	4-1/8 in (105 mm)	1-9/32 in (32 mm)	1 in (25 mm)	14-1/16 in (357 mm)
54-024	24 oz (680 g)	4-3/4 in (121 mm)	1-1/2 in (38 mm)	1-1/8 in (29 mm)	15-1/16 in (382 mm)
54-032	32 oz (907 g)	4-15/16 in (125 mm)	1-21/32 in (42 mm)	1-5/16 in (33 mm)	16 in (406 mm)
54-040	40 oz (1134 g)	5-3/16 in (132 mm)	1-11/16 in (43 mm)	1-1/4 in (32 mm)	16 in (406 mm)
54-048	48 oz (1361 g)	5-1/2 in (140 mm)	2 in (51 mm)	1-35/64 in (39 mm)	16 in (406 mm)



STANLEY® FATMAX® ANTIVIBE® ENGINEER HAMMER



- Ideal for striking wood, metal or stone.
- AntiVibe® technology minimizes vibration and shock at impact.
- Exclusive rim temper reduces incidences of chipping or spalling.
- Forged, one-piece steel construction for strength and durability.
- Slip-resistant handle for a secure grip and comfort.
- Precision balanced.



Product #	Head Weight	Head Length	Face Width	Overall Length
56-004	3 lbs (1.36 kg)	5 in (127 mm)	1-39/64 in (41 mm)	15 in (381 mm)

STANLEY® JACKETED FIBERGLASS ENGINEER HAMMERS

- Ideal for striking wood, metal or stone.
- Fiberglass core adds strength and durability in the handle, reduces vibrations and provides the “feel of wood”.
- Yellow-colored shaft for easy product visibility.
- Exclusive rim temper reduces incidences of chipping or spalling.



Product #	Head Weight	Head Length	Face Width	Overall Length
56-202	2.5 lbs (1.13 kg)	4-5/32 in (105 mm)	1-21/32 in (42 mm)	13-3/4 in (349 mm)
56-204	4 lbs (1.81 kg)	4-31/32 in (127 mm)	1-29/32 in (48 mm)	14 in (356 mm)

STANLEY® HICKORY HANDLE ENGINEER HAMMERS

- Forged head is heat-treated and tempered for increased durability.
- Traditional, high quality hickory handle.
- Machined finished faces.



Product #	Head Weight	Head Length	Face Width	Overall Length
56-803	3 lbs (1.36 kg)	4-7/16 in (113 mm)	1-3/4 in (44 mm)	13-3/4 in (349 mm)
56-804	4 lbs (1.81 kg)	5 in (122 mm)	1-29/32 in (48 mm)	15-3/4 in (400 mm)

STANLEY® FATMAX® ANTIVIBE® BLACKSMITH HAMMER



- Ideal for striking unhardened metals.
- AntiVibe® technology minimizes vibration and shock at impact.
- Exclusive rim temper reduces incidences of chipping or spalling.
- Forged, one-piece steel construction for strength and durability.
- Slip-resistant handle for a secure grip and comfort.
- Precision balanced.



Product #	Head Weight	Head Length	Face Width	Overall Length
56-003	2 lbs (0.91 kg)	5-1/8 in (130 mm)	1-3/8 in (35 mm)	14 in (356 mm)



STANLEY® JACKETED FIBERGLASS BLACKSMITH HAMMERS

- Ideal for striking unhardened metals.
- Fiberglass core adds strength and durability in the handle, reduces vibrations and provides the “feel of wood”.
- Exclusive rim temper reduces incidences of chipping or spalling.



Product #	Head Weight	Head Length	Face Width	Overall Length
56-218	2.5 lbs (1.13 kg)	5-1/8 in (130 mm)	1-39/64 in (41 mm)	13-5/8 in (347 mm)
56-220	4 lbs (1.81 kg)	5-3/4 in (146 mm)	1-13/16 in (46 mm)	13-15/16 in (354 mm)

STANLEY® FATMAX® ANTIVIBE® DRILLING HAMMER



- Ideal for striking chisels, punches, start drills and unhardened metals.
- AntiVibe® technology minimizes vibration and shock at impact.
- Exclusive rim temper reduces incidences of chipping or spalling.
- Forged, one-piece steel construction for strength and durability.
- Slip-resistant handle for a secure grip and comfort.
- Precision balanced.



Product #	Head Weight	Head Length	Face Width	Overall Length
56-001	3 lbs (1.36 kg)	4 in (102 mm)	1-1/2 in (38 mm)	11 in (279 mm)

STANLEY® JACKETED FIBERGLASS DRILLING HAMMERS

- Ideal for striking chisels, punches, start drills and unhardened metals.
- Fiberglass core adds strength and durability in the handle, reduces vibrations and provides the “feel of wood”.
- Yellow-colored shaft for easy product visibility.
- Exclusive rim temper reduces incidences of chipping or spalling.



Product #	Head Weight	Head Length	Face Width	Overall Length
56-701	2 lbs (0.9 kg)	3-13/16 in (97 mm)	1-3/8 in (35 mm)	10-1/2 in (267 mm)
56-705	3 lbs (1.36 kg)	4-1/2 in (114 mm)	1-9/16 in (40 mm)	10-3/4 in (273 mm)

STANLEY® HICKORY HANDLE DRILLING HAMMER

- Forged steel head is hardened and tempered.
- Faces are machine finished.
- Hickory handle is finished with clear lacquer.



Product #	Head Weight	Head Length	Face Diameter	Overall Length
56-703	3 lbs (1.36 kg)	4-3/8 in (111 mm)	1-5/8 in (42 mm)	10-1/2 in (267 mm)



STANLEY® FATMAX® ANTIVIBE® BRICKLAYER'S HAMMER



- Ideal for cutting and setting brick, stone or masonry.
- AntiVibe® technology minimizes vibration and shock at impact.
- Exclusive rim temper reduces incidences of chipping or spalling.
- Forged, one-piece steel construction for strength and durability.
- Slip-resistant handle for a secure grip and comfort.
- Precision balanced.



Product #	Head Weight	Head Length	Face Width	Overall Length
54-022	20 oz (567 g)	6-3/4 in (171 mm)	15/16 in (24 mm)	11 in (279 mm)

STANLEY® HICKORY HANDLE BRICKLAYER'S HAMMER

- Heat-treated, high-carbon steel head.
- Fully polished head.
- Traditional, high quality hickory handle.
- Double wedge head-to-handle assembly for secure fit.
- Rim tempered face reduces incidences of chipping or spalling.
- Cutting edge is used for cutting (splitting) brick.



Product #	Head Weight	Head Length	Face Width	Overall Length
54-435	24 oz (680 g)	8 in (203 mm)	1-1/8 in (29 mm)	11-3/8 in (288 mm)



STANLEY® FATMAX® ANTIVIBE® SHINGLER'S HATCHET WITH BLADE



- Ideal for installing shingles and other roofing material.
- Blade ideal for cutting roofing materials.
- AntiVibe® technology minimizes vibration and shock at impact.
- Exclusive rim temper reduces incidences of chipping or spalling.
- Forged, one-piece steel construction for strength and durability.
- Slip-resistant handle for a secure grip and comfort.
- Precision balanced.



Product #	Head Weight	Head Length	Face Width	Overall Length
54-028	15 oz (425 g)	6-3/16 in (158 mm)	1-15/32 in (37 mm)	12-3/4 in (324 mm)

STANLEY® FATMAX® ANTIVIBE® DRYWALL HAMMER



- Ideal for installing drywall or gypsum board.
- AntiVibe® technology minimizes vibration and shock at impact.
- Exclusive rim temper reduces incidences of chipping or spalling.
- Forged, one-piece steel construction for strength and durability.
- Slip-resistant handle for a secure grip and comfort.
- Precision balanced.



Product #	Head Weight	Head Length	Face Diameter	Overall Length
54-015	14 oz (397 g)	5-3/4 in (146 mm)	1-1/2 in (38 mm)	13-5/8 in (341 mm)

STANLEY® MAGNETIC TACK HAMMER

- Ideal for holding and driving tacks and brads.
- Polished face and magnetic tip.
- Hickory handle for durability.



Product #	Head Weight	Head Length	Face Diameter	Overall Length
54-304	5 oz (142 g)	4-5/16 in (110 mm)	9/16 in (14 mm)	10-5/16 in (262 mm)

STANLEY® HICKORY HANDLE SOFT-FACE HAMMERS

- Soft face helps minimize marring and surface damage.
- Faces are made of durable plastic that is ideal for fine finished surfaces.
- Plastic faces are replaceable.
- Hickory handle for durability.



Product #	Head Weight	Head Length	Face Diameter	Overall Length
57-594	8 oz (227 g)	3-27/32 in (97 mm)	1-13/64 in (31 mm)	12-1/8 in (308 mm)
57-595	16 oz (454 g)	5 in (126 mm)	1-5/16 in (33 mm)	13-5/8 in (346 mm)



STANLEY® RUBBER MALLETS

- Rubber head helps minimize marring and surface damage.
- Tough rubber head molded to a wood handle.



Product #	Head Weight	Head Length	Face Diameter	Overall Length
51-104	16 oz (454 g)	3-7/8 in (98 mm)	2-1/2 in (64 mm)	13-1/2 in (343 mm)
57-522	18 oz (510 g)	3-7/8 in (98 mm)	2-3/8 in (60 mm)	13-1/2 in (343 mm)

STANLEY® COMPO-CAST® BALL PEIN HAMMERS

- Forged and heat-treated head for increased durability.
- Rim tempered head reduces incidences of chipping or spalling.
- Non-sparking, chemical resistant molded urethane covering.
- The head is filled with steel shot to eliminate bounce back for dead blow action.



Product #	Head Weight	Head Length	Face Diameter	Ball Pein Diameter	Overall Length
54-516	16 oz (454 g)	4-1/8 in (105 mm)	1-1/4 in (32 mm)	1 in (25 mm)	12-11/16 in (322 mm)
54-524	24 oz (680 g)	4-7/16 in (113 mm)	1-1/2 in (38 mm)	1-3/16 in (30 mm)	12-15/16 in (329 mm)
54-532	32 oz (907 g)	4-3/4 in (121 mm)	1-11/16 in (43 mm)	1-1/4 in (32 mm)	13-3/4 in (349 mm)

STANLEY® COMPO-CAST® STANDARD SOFT-FACE HAMMERS

- Uni-Cast™ construction of non-ferrous materials eliminates sparking and won't absorb liquids.
- No exposed metal on face, head or shaft.
- Dead blow function eliminates bounceback when striking hardened surfaces.
- Soft face helps prevent marring.
- Steel reinforced handle provides strength and resists breaking on overstrike.



Product #	Head Weight	Head Length	Face Diameter	Overall Length
57-530	10 oz (284 g)	3-1/8 in (79 mm)	1-13/64 in (31 mm)	10-1/8 in (257 mm)
57-531	18 oz (510 g)	3-3/4 in (95 mm)	1-3/4 in (44 mm)	11-3/8 in (290 mm)
57-532	21 oz (595 g)	4-1/16 in (103 mm)	2 in (51 mm)	13 in (330 mm)
57-533	42 oz (1191 g)	4-5/8 in (117 mm)	2-15/32 in (62 mm)	14-3/8 in (365 mm)
57-534	52 oz (1474 g)	5-1/2 in (140 mm)	2-13/16 in (71 mm)	15-1/4 in (387 mm)

STANLEY® COMPO-CAST® SLIMLINE SOFT-FACE HAMMERS

- Slimline model offers unique profile for assembly and repair applications in confined areas.
- Uni-Cast™ construction of non-ferrous materials eliminates sparking and won't absorb liquids.
- No exposed metal on face, head or shaft.
- Dead blow function eliminates bounceback when striking hardened surfaces.
- Soft face helps prevent marring.
- Steel reinforced handle provides strength and resists breaking on overstrike.



Product #	Head Weight	Head Length	Face Diameter	Overall Length
57-540	5 oz (142 g)	2-15/16 in (74 mm)	29/32 in (23 mm)	9-1/2 in (241 mm)
57-541	14 oz (397 g)	4-3/16 in (106 mm)	1-19/64 in (33 mm)	10-1/2 in (267 mm)
57-542	18 oz (510 g)	4-1/4 in (108 mm)	1-33/64 in (38 mm)	12-1/8 in (308 mm)
57-543	21 oz (595 g)	5-1/4 in (133 mm)	1-17/32 in (39 mm)	12-7/8 in (327 mm)

STANLEY® COMPO-CAST® SOFT-FACE SLEDGE HAMMERS

- Non-sparking, soft-face sledgehammers.
- Uni-Cast™ construction of non-ferrous materials eliminates sparking and won't absorb liquids.
- No exposed metal on face, head or shaft.
- Dead blow function eliminates bounceback when striking hardened surfaces.
- Soft face helps prevent marring.
- Steel reinforced handle provides strength and resists breaking on overstrike.
- Urethane covering helps reduce noise.
- Flat area on head allows upright storage.



Product #	Head Weight	Head Length	Face Diameter	Overall Length
57-550	5 lbs (2.26 kg)	7 in (178 mm)	2-55/64 in (73 mm)	19-5/8 in (498 mm)
57-551	8 lbs (3.62 kg)	7-1/8 in (181 mm)	2-61/64 in (75 mm)	29-7/8 in (759 mm)
57-552	10.5 lbs (4.76 kg)	8-1/8 in (206 mm)	3-25/64 in (86 mm)	29-7/8 in (759 mm)
57-554	11.5 lbs (5.21 kg)	8-1/8 in (206 mm)	3-25/64 in (86 mm)	36-18 in (918 mm)

STANLEY® HICKORY HANDLE SLEDGE HAMMERS

- Forged head is heat-treated and tempered for increased durability.
- Traditional, high quality hickory handle.



Product #	Head Weight	Head Length	Face Diameter	Overall Length
56-808	8 lbs (3.62 kg)	6-7/16 in (164 mm)	2-5/16 in (59 mm)	34-1/4 in (870 mm)
56-810	10 lbs (4.53 kg)	7-1/8 in (181 mm)	2-3/8 in (60 mm)	35 in (889 mm)
56-812	12 lbs (5.44 kg)	7-1/2 in (191 mm)	2-5/8 in (67 mm)	35 in (889 mm)
56-816	16 lbs (7.25 kg)	8-3/8 in (213 mm)	2-13/16 in (71 mm)	35 in (889 mm)

