

ProTac HL® 5-X USB / ProTac HL® 5-X

MULTI FUEL - 18650 USB LI-ION RECHARGEABLE or 4x CR123A FLASHLIGHT

MARKET
APPLICATIONS: Law Enforcement, Security, Emergency Medical Services, Sporting Goods, Hardware/Tool, Consumer

DESCRIPTION: The ProTac HL® 5-X USB or ProTac HL® 5-X are 3,500 lumen tactical flashlights that can use either two proprietary Streamlight 18650 USB rechargeable Li Ion batteries or four CR123A disposable batteries. The ProTac HL® 5-X USB is a complete rechargeable system that comes with a charge cord and two 18650 button top batteries that feature integrated micro-USB charge ports. The ProTac HL® 5-X comes packaged with four CR123A batteries. They are the newest and brightest addition to the ProTac® series. They offer the latest in power LED technology and three different user selectable programs. The lights will accept two battery types, two Streamlight 18650 Li Ion rechargeable batteries or four CR123A batteries. The output from the C4® LED results in one of the brightest tactical lights available. The “sure grip rubber sleeve” and included lanyard ensures you’ll never lose your grip.

CASE MATERIAL: 6000 series machined aircraft aluminum with anodized finish. Available in Black.

DIMENSIONS: Length: 9.53 in. (23.65 cm) Barrel Diameter: 1.24 in. (3.15 cm)
 Head Diameter: 2.35 in. (5.97 cm) Tri-Lobe Diameter: 2.29 in. (5.81 cm)
WEIGHT: ProTac HL® 5-X USB: 1 lb 3.4 oz (550 grams) with two Streamlight 18650 USB Li-Ion batteries (included in purchase)
 ProTac HL® 5-X: 1 lb 2.4 oz (522 grams) with four CR123A batteries (included in purchase)

LENS: Glass lens with anti-reflective coating, gasket sealed.

LIGHT SOURCE: C4® LED technology, impervious to shock with a 50,000 hour lifetime. Total internal reflection optic.

LIGHT OUTPUT: See charts. Optimized electronics provides thermal management and regulated intensity.

ON/OFF: Multi-function, easy access head mounted push-button switch. One handed operation of momentary, variable intensity or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe/low (factory default), high only, or low/med/high.


RUN TIME: See chart. All claims to 10% of initial lumen output.

BATTERY: Two Streamlight 18650 USB Li-Ion protected 3.7V 2600 mAh rechargeable batteries, recharges in 5 hours. Four (4) 3 Volt CR123A lithium batteries with a storage life of 10 years.

FEATURES:









 C4® LED technology for extreme brightness.
 IPX7 rated design; waterproof to 1 meter for 30 minutes.
 1 meter impact resistance tested.
 LED Solid State Power Regulation provides maximum light output throughout battery life.
 TEN-TAP® programmable switch allows user to select one of three different programs.
 Anti-roll face cap.
 Sure grip rubber sleeve.
 Serialized for positive identification.

WARRANTY: Streamlight's Limited Lifetime Warranty

APPROVALS:  Meets applicable European Community directives.

 CEC Compliant (ProTac HL® 5-X USB only)

OPTIONAL
ACCESSORIES: Holster, Charge Cords

	WITH CR123A BATTERIES				WITH 18650 RECHARGEABLE BATTERIES			
	FL1 STANDARD	HIGH	MEDIUM	LOW	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		2500 LUMENS	1000 LUMENS	250 LUMENS		3500 LUMENS	1000 LUMENS	250 LUMENS
RUNTIME		1h 30m	2h 30m	10h 30m		1h 15m	3h	11h 30m
DISTANCE		385m	237m	120m		452m	237m	120m
INTENSITY		37,000cd	14,100cd	3,620cd		51,000cd	14,100cd	3,620cd

Strobe Runtime: 1.5 hours

Strobe Runtime: 1.25 hours

All performance claims tested to ANSI/PLATO FL1-2016 Standard

Issued: 12/18/2017

Revised: 12/21/2017

Rev: 1

Made In China

Document #321