



A210403

Chain Roof Anchor

FEATURES

- Minimum Breaking Strength (MBS) 5,000 lb
- 2 inch connector ring
- Fastening holes for nails and lag screws
- Installs on flat and pitched roofs
- Durable, zinc-coated, steel construction
- 360 degree loading with lag screws
- Meets OSHA 1910.140 and 1926.502



SPECIFICATIONS

Model No.	Material	Length	Width	Connection Size	Minimum Breaking Strength (MBS)	Approx. Weight	Compliance Standards
A210403	Zinc Plated Steel, Rubber	25.5 in (643 mm)	3 in (76 mm)	2 in (51 mm)	Lag Screws - 5,000 lbs (22.2 kN) Nails - 3600 lbs (16.0 kN)	1.94 lbs (0.88 kg)	OSHA 1910 & 1926

*See User Instructions for more information.

⚠ WARNING: Compliant fall protection equipment must only be used as it was designed and adhere to the hierarchy of controls as discussed in ANSI Z359.2. Users MUST read and follow all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to heed these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

Technical Data Sheet