



A311000

EVO Remote Anchor System

FEATURES

- Minimum Breaking Strength (MBS): 5,000 pounds
- 2 inch steel swivel D-ring
- Concrete applications
- Precast anchor receptacles for wood and metal decking applications
- Remote grab system to install the anchor from the ground
- Meets ANSI Z359.18-2017
- Meets OSHA 1910.140 and 1926.502 requirements



SPECIFICATIONS

Model No.	Primary Material	Purpose	Mounting Substrate	Product Length	Minimum Breaking Strength (MBS)	Approx. Weight	Compliance Standards
A311000	Steel Cable	Anchor	Receptacle in Concrete	10 3/4 in (273 mm)	5,000 lbs (22.2 kN)	0.75 lbs (0.34 kg)	ANSI Z359.18-2017 OSHA 1910 & 1926
A312000	Aluminum	Remote Grab	N/A	3 3/4 in (95 mm)	N/A	1.0 lbs (0.45 kg)	N/A
A313000	Steel	Receptacle	Wood	4 1/4 in (108 mm)	5,000 lbs (22.2 kN)	0.66 lbs (0.30 kg)	ANSI Z359.18-2017 OSHA 1910 & 1926
A314000	Steel	Receptacle	Metal	5 1/2 in (140 mm)	5,000 lbs (22.2 kN)	1.28 lbs (0.58 kg)	ANSI Z359.18-2017 OSHA 1910 & 1926

*See User Instructions for more information.

⚠ WARNING: Compliant fall protection equipment must only be used as it was designed and adhere to the hierarchy of controls as discussed in ANSI Z359.2. Users MUST read and follow all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to heed these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

Technical Data Sheet