



A410400

Strut Channel Anchor

FEATURES

- Minimum Breaking Strength (MBS) 5,000 lb
- Durable, zinc-coated, steel construction
- Compatible with standard 1 $\frac{5}{8}$ inch, 12 gauge or thicker, strut channel
- Meets ANSI Z359.18-2017, Type A
- Meets OSHA 1910.140 and 1926.502



Steel Channel Anchor
 Model A410400
 Part 1249121 MFG 03/2022
**DO NOT REMOVE
 INSPECT BEFORE USE**

Maximum Service Temperature: 302°
 Refer to user instructions for direction
 of loading restrictions.
 This Product meets the standards as marked:
 OSHA 1910.140 & 1926.502
 ANSI Z359.18-2017, Type A
 EN 12842 01 181 A

SPECIFICATIONS

Model No.	Material	Length	Width	Height	Connection Size	Minimum Breaking Strength (MBS)	Approx. Weight	Compliance Standards
A410400	Zinc Plated Steel	4 in (102 mm)	1.4 in (36 mm)	2 in (76 mm)	.46 in (51 mm)	5,000 lbs (22.2 kN)	0.62 lbs (0.28 kg)	ANSI Z359.18-2017 Type A OSHA 1910 & 1926

*See User Instructions for more information.

⚠ WARNING: Compliant fall protection equipment must only be used as it was designed and adhere to the hierarchy of controls as discussed in ANSI Z359.2. Users MUST read and follow all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to heed these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

Technical Data Sheet