



# A515000

## Reusable Concrete Anchorage Connector with 2 inch Swivel D-ring

### FEATURES

- Minimum Breaking Strength (MBS): 5,000 pounds
- 2 inch steel swivel D-ring
- Concrete applications
- Hole plug
- Multi-directional use
- Meets ANSI Z359.18-2017
- Meets OSHA 1910.140 and 1926.502 requirements



### SPECIFICATIONS

Model No.	Cable Material	Connection Size	Mounting Hole Dia.	Product Length	Minimum Breaking Strength (MBS)	Approx. Weight	Compliance Standards
A515000	Steel	2 in (51 mm)	3/4 in (19 mm)	12 3/4 in (324 mm)	5,000 lbs (22.2 kN)	1.0 lbs (0.45 kg)	ANSI Z359.18-2017 OSHA 1910 & 1926

\*See User Instructions for more information.

**⚠ WARNING:** Compliant fall protection equipment must only be used as it was designed and adhere to the hierarchy of controls as discussed in ANSI Z359.2. Users MUST read and follow all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to heed these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

# Technical Data Sheet