### **Post Anchor**

#### **FEATURES**

- Minimum Breaking Strength (MBS): 5,000 lb
- Corrosion resistant galvanized steel construction
- Fastening holes for wood and concrete
- Fastens to I-beams with backer plate (A525405)
- 360 degree loading direction
- Meets ANSI Z359.18-2017
- Meets OSHA 1910.140 and 1926.502 requirements



#### **SPECIFICATIONS**

Model No.	Material	Length	Width	Height	Plate Thickness	Approx. Weight
A525400	Galvanized	16 in	16 in	14.9 in	3/8 in	38 lbs
	Steel	(406 mm)	(406 mm)	(378 mm)	(9.5 mm)	(17.2 kg)

## **COMPLIANCE STANDARDS**

Meets	Minimum Breaking Strength		
ANSI Z359.18-2017	5000 lb (22 kN)		
OSHA 29 CFR 1910.140 & 1926.502	5000 lb (22 kN)		

\*See User Instructions for more information.

MARNING: Compliant fall protection equipment must only be used as it was designed and adhere to the hierarchy of controls as discussed in ANSI Z359.2. Users MUST read and follow all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to heed these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

# **Technical Data Sheet**