



FALL PROTECTION

BANTAM 8' LEADING EDGE

Compact and Versatile Leading Edge Protection

- Meets ANSI z359.14 SRD-LE
- Supports worker up to 400 lbs
- Tested and approved over steel beam, B-Deck and precast concrete



www.wernerco.com





BANTAM 8' LEADING EDGE



SRL Performance

Leading Edge

- Meets ANSI z359.14 SRD-LE Requirements

Minimal Clearances

- Class A < 24" when used overhead
- Tested and approved over steel beam, B-Deck and precast concrete

Supports worker up to 400 lbs.

INTEGRATED HARNESS FIT



Harness Pin Attachment

- Low profile fits easily behind harness D-ring
- Secure dual action open and close



Energy Absorber Pack

- Compact, low profile design
- Integrates into harness back pad
- Secures to harness torso straps
- Provides cushion for SRL contact with back

SPECIFICATIONS

MODEL NO.	LENGTH	SINGLE OR TWINLEG	HOUSING	HOUSING CONNECTOR	LIFELINE CONSTITUENT	LIFELINE CONNECTOR
R410008LE	8'	Single	Thermoplastic	Harness Web Connector	3/16 Galvanized Steel Cable	Steel Swivel Snap Hook
R410008LE-R	8'	Single	Thermoplastic	Harness Web Connector	3/16 Galvanized Steel Cable	Aluminum Rebar Hook
R410008LE-SR	8'	Single	Thermoplastic	Harness Web Connector	3/16 Galvanized Steel Cable	Steel Form Hook
R413008LE	8'	Twinleg	Thermoplastic	Harness Web Connector	3/16 Galvanized Steel Cable	Steel Swivel Snap Hook
R413008LE-R	8'	Twinleg	Thermoplastic	Harness Web Connector	3/16 Galvanized Steel Cable	Aluminum Rebar Hook
R413008LE-SR	8'	Twinleg	Thermoplastic	Harness Web Connector	3/16 Galvanized Steel Cable	Steel Form Hook