



# FALL PROTECTION

## MAX PATROL CLASS 1

### NEW ANSI Code Compliance

#### IMPROVED SRLS MEET ANSI Z359.14-2021

- Maximum Freedom of Movement
- Provides clear identification of Class I: Overhead Only (Dorsal D-Ring height or above)
- 24" Max Arrest Distance
- 400lb Capacity per OSHA

#### VISUAL DIFFERENTIATION



### Web



1 inch UHMWPE / polyester webbing

Lightweight & Rugged Design

### Cable



3/16 in Galvanized Cable

20', 30', and 50' Working Lengths

Visual differentiation provides clear identification Class 1: Overhead Only (Dorsal D-Ring height or above) (Blue)

Durable recessed labels are protected to aid inspection

The industry's best carry handle for better transportation, aiding in productivity

### SPECIFICATIONS

MODEL NO.	LENGTH	HOUSING	HOUSING CONNECTOR	LIFELINE CONSTITUENT	LIFELINE CONNECTOR	WEIGHT
R430011	11'	Thermoplastic	Steel Carabiner	1 in UHMWPE / polyester webbing	Steel Snap Hook	3.5 lbs
R430011-R	11'	Thermoplastic	Steel Carabiner	1 in UHMWPE / polyester webbing	Aluminum Rebar Hook	3.9 lbs
R430011-SR	11'	Thermoplastic	Steel Carabiner	1 in UHMWPE / polyester webbing	Steel Rebar Hook	4.2 lbs
R410010	10'	Thermoplastic	Steel Carabiner	Galvanized Steel Cable	Steel Snap Hook	4.2 lbs
R410020	20'	Thermoplastic	Steel Carabiner	Galvanized Steel Cable	Swivel Snap Hook	8.2 lbs
R410030	30'	Thermoplastic	Steel Carabiner	Galvanized Steel Cable	Swivel Snap Hook	9.9 lbs
R410050	50'	Thermoplastic	Steel Carabiner	Galvanized Steel Cable	Swivel Snap Hook	14.7 lbs



WERNERCO.COM





# FALL PROTECTION

## MAX PATROL CLASS 2

### NEW ANSI Code Compliance

#### IMPROVED SRLS MEET ANSI Z359.14-2021

- Maximum Freedom of Movement
- The SRL is tested and approved for use over steel beam, precast concrete, and b-deck
- Provides clear identification of Class 2: Overhead, Foot Level, Leading Edge
- 24" Max Arrest Distance when used overhead
- 400lb Capacity per OSHA



Visual differentiation provides clear identification Class 2: Overhead, Foot Level, Leading Edge (Yellow)

Thermoplastic Housing with swivel top

3/16 in Galvanized Cable

Durable recessed labels are protected to aid inspection

20', 30' and 50' Working Lengths

Lightweight & Rugged Design approved for use over steel beam, precast concrete and b-deck

The industry's best carry handle for better transportation, aiding in productivity



### SPECIFICATIONS

MODEL NO.	LENGTH	HOUSING	HOUSING CONNECTOR	LIFELINE CONSTITUENT	LIFELINE CONNECTOR	WEIGHT
R410020LE	20'	Thermoplastic	Steel Carabiner	Galvanized Cable	Snap Hook	8.8 lbs
R410030LE	30'	Thermoplastic	Steel Carabiner	Galvanized Cable	Snap Hook	10.5 lbs
R410050LE	50'	Thermoplastic	Steel Carabiner	Galvanized Cable	Snap Hook	15.3 lbs
R410065LE	65'	Thermoplastic	Steel Carabiner	Galvanized Cable	Snap Hook	23.5 lbs