

**PRODUCT INFORMATION**

<b>Style:</b>	<b>Y9266</b>		
<b>Sizing:</b>	<u>Size</u>	<u>Part #</u>	<u>Overedge</u>
	XSmall	Y9266XS	Blue
	Small	Y9266S	White
	Medium	Y9266M	Green
	Large	Y9266L	Gray
	XLarge	Y9266XL	Orange
<b>Registered Brand Name:</b>	FlexTech™		
<b>Classification:</b>	Palm Dip		



**PRODUCT DESCRIPTION**

<b>Description:</b>	High Performance Polyethylene Fiber (HPPE) Palm Coated Glove
<b>Color:</b>	White Shell / White Palm
<b>Shell:</b>	Seamless Knit High Performance Polyethylene Fiber (HPPE)
<b>Palm Coating:</b>	Polyurethane This Glove is Silicone Free
<b>Sold by:</b>	Dozen Pair
<b>Packaging (Inner Pack):</b>	12 Pairs
<b>Packaging (Case Pack):</b>	144 Pairs

**CUT PROTECTION PERFORMANCE INFORMATION**

<b>Test Method:</b>	ASTM 1790-97
<b>Test Results:</b>	753 grams / 1.66 lbs ANSI Cut Level 2
<b>Test Method:</b>	ASTM F2992-15
<b>Test Results:</b>	420 Grams ANSI Level A1

**ABRASION PROTECTION PERFORMANCE INFORMATION**

<b>Test Method:</b>	ASTM D3389-10
<b>Test Results:</b>	Level 5 10,757 Cycles

**CE EN 388 STANDARD**

<b>EN Abrasion Resistance:</b>	§ 6.1	Level 4
<b>EN Cut Resistance:</b>	§ 6.2	Level 3
<b>EN Tear Resistance:</b>	§ 6.3	Level 4
<b>EN Puncture Resistance:</b>	§ 6.4	Level 2

**PARTICLE TESTING INFORMATION**

<b>Test Method:</b>	Helmke Drum Particle Testing (IEST-RP-CC003.3, Appendix B, Section B.2.5)
<b>Test Results:</b>	P>0.3um/sq.ft. = Category III P>0.5um/sq.ft. = Category III

**WASHING INSTRUCTIONS**

Machine wash in warm water with detergent or soap for 10-15 minutes. Water temperature should not exceed 140°F (60°C). Rinse in cold water. Tumble dry low for 15-20 minutes, not exceeding 120°F (50°C). For heavily soiled gloves pre-treat with a stain remover. Do not use bleach or dry cleaning solution.

**CAUTION**

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.