



3/4" DRIVE SHALLOW IMPACT SOCKETS, 6 POINT, METRIC

Black Industrial Finish

TOOLS @ HEIGHT
DROP PREVENTION SYSTEM


Side hole in socket permits use with Snap-on Industrial Brands Tools@Height drive tools such as ratchets, extensions and u-joints



6M-617A



MS-6-8H



Product Code	Size (MM)	A		B		C		D		E		F		Uses RET RING® Number	Use O-Ring / Pin
		OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)							
6M-617A	17	2	1 5/8	1 7/32	17/32	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1	6-1XS	6-1A / 6-2B	
6M-619A	19	2	1 5/8	1 1/4	17/32	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1	6-1XS	6-1A / 6-2B	
6M-620A	20	2	1 5/8	1 3/8	35/64	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1	6-1XS	6-1A / 6-2B	
6M-622A	22	2	1 5/8	1 1/2	19/32	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1	6-1XS	6-1A / 6-2B	
6M-624A	24	2	1 5/8	1 35/64	11/32	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1	6-1XS	6-1A / 6-2B	
6M-627A	27	2	1 5/8	1 11/16	3/4	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 5/16	6-1XS	6-1A / 6-2B	
6M-630	30	2 3/32	1 5/8	1 27/32	47/64	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 13/32	6-1XS	6-1A / 6-2B	
6M-631	31	2 1/8	1 5/8	1 15/16	3/4	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 7/16	6-1XS	6-1A / 6-2B	
6M-632	32	2 1/8	1 3/4	2	13/16	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 7/16	6-1XS	6-1A / 6-2C	
6M-634	34	2 1/8	1 3/4	2	7/8	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 7/16	6-1XS	6-1A / 6-2C	
6M-635	35	2 1/4	1 3/4	2 1/8	7/8	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 9/16	6-1XS	6-1A / 6-2C	
6M-636	36	2 1/4	1 3/4	2 1/8	7/8	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 9/16	6-1XS	6-1A / 6-2C	
6M-638	38	2 1/4	1 3/4	2 1/4	15/16	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 9/16	6-1XS	6-1A / 6-2C	
6M-641	41	2 5/8	1 3/4	2 13/32	1 1/8	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 15/16	6-1XS	6-1A / 6-2C	
6M-646	46	2 5/8	1 3/4	2 19/32	1 1/8	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 15/16	6-1XS	6-1A / 6-2C	

MS-6-8H 8 Piece 3/4" Drive Shallow 6 Point Impact Socket Set on Clip Rail

Contents Include:

Product Code	Size (MM)	Product Code	Size (MM)	Product Code	Size (MM)
6M-619A	19	6M-627A	27	6M-636	36
6M-622A	22	6M-630	30	6M-641	41
6M-624A	24	6M-632	32		

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.
- Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.
- Drive end features pin retention hole and groove.



3/4" DRIVE ONE PIECE IMPACT HEX BIT DRIVERS, MM

Black Industrial Finish

Product Code	Hex Size (MM)	Overall Length (Inches)	Drive End Diameter (Inches)	Nose Length	Uses RET Ring	
					Number	use O-Ring/Pin
35810	10	3 1/2	1 3/4	3/4	6-1XS	6-1A/6-2C
35812	12	3 1/2	1 3/4	3/4	6-1XS	6-1A/6-2C
35814	14	3 1/2	1 3/4	3/4	6-1XS	6-1A/6-2C
35817	17	3 1/2	1 3/4	3/4	6-1XS	6-1A/6-2C
35819	19	3 1/2	1 3/4	3/4	6-1XS	6-1A/6-2C
35821	21	3 1/2	1 3/4	3/4	6-1XS	6-1A/6-2C
35824	24	3 1/2	1 3/4	3/4	6-1XS	6-1A/6-2C
35827	27	3 1/2	1 3/4	3/4	6-1XS	6-1A/6-2C
35830	30	3 1/2	1 3/4	3/4	6-1XS	6-1A/6-2C
35832	32	3 1/2	1 3/4	3/4	6-1XS	6-1A/6-2C

Fed. Spec: ANSI B107.2

38936 10 Piece 3/4" Drive One Piece Impact Hex Bit Drivers, MM

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
35810	10	35819	19	35830	30
35812	12	35821	21	35832	32
35814	14	35824	24		
35817	17	35827	27		



35812

35830



38936